



jalas® E-SPORT 1625

EN ISO 20345:2022 S3S, CI, HI, FO, LG ASTM F2413-18 M/I/C SD 35 PR

Learn more

Safety boot, nail protection material plasma-treated composite (PTC) textile, toecap material aluminium, plastic shank, PU outsole, upper material PU-coated leather;Split leather

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Good shock absorption
- Light

FUNCTIONS

- Padded boot shaft
- Oil-resistant outsole
- Anti-static properties
- Water repellent
- Ventilating insole
- Low weight
- Bellows tongue
- Conforms with IEC 61340-5-1 (ESD)
- Reflector
- Double shock absorption zones

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION E-Sport
UPPER MATERIAL PU-coated leather, Split leather
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE FX2 Classic
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Shock absorption zone in Ergothan
OUTSOLE MATERIAL PU outsole
FASTENING Laces
COLOUR Black, Grey, Red
NET WEIGHT, (SIZE 42) 1.21 kg

COMPLIANCE

CE Cat. II

EN ISO 20345:2022
S3S, CI, HI, FO, LG

EAC TP TC 019:2011

ASTM F2413-18
M/I/C
SD 35 PR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Water repellent
- Nail protection in plasma-treated composite (PTC) textile

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1625-36	6408487438639
37	4	5	6	1625-37	6408487438646
38	5	5½	6½	1625-38	6408487438653
39	6	6½	7½	1625-39	6408487438660
40	6½	7½	8½	1625-40	6408487438677
41	7	8	9	1625-41	6408487438684
42	8	9	10	1625-42	6408487438691
43	9	9½	11	1625-43	6408487438707
44	10	10½	11½	1625-44	6408487438714
45	10½	11	12½	1625-45	6408487438721
46	11	12	13	1625-46	6408487438738
47	12	13	14	1625-47	6408487438745

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.