Specifications

Eaton C10G2

Catalog Number: C10G2

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 2 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C10G2

EAN
5027590493468

UPC
051712754224

Product Length/Depth
38 mm

Product Height
10 mm

Product Width
10 mm

Product Weight
8.2 g

Compliances
RoHS Compliant
CE Marked
GoST-R

Certifications
IEC 60269

Powering Business Worldwide

Electrical data

Amperage Rating

2 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Utilization category

gL/gG (cable protection/equipment protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CHM Modular fuse holder

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia