DATASHEET - ED315M400



Fuse-link, LV, 315 A, AC 415 V, BS88/B3, BS88/B4, 38 x 136 mm, gM, BS, 315M400

Catalog No. **ED315M400**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	315
Motor current rating	I	A	315M400
Rated voltage			AC 415 V
Construction size			BS88/B3 BS88/B4
Size			38 x 136 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			centre-bolted tags
Standards/Regulations			BS88-2 IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	315
Rated voltage		V	415
Voltage type			AC
Rated switching capacity		kA	80
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/1088bed5-fd8e-4b3e-96f0-f749b5af5f88.pdf

© 12/2018 by Eaton Industries GmbH