Date: 22/01/2024

A-1200 ; 0...40 bar gauge; one switching output (PNP)

A-1200 ; 0...40 bar gauge; one switching output (PNP)

Item number:	46967534	
Quantity:	1 pcs.	
Order code:	A-1200-D-BG440-1GI1-3K1HI-M4ZZS-ULZZ	W1011A12-ZZPSIOW-GSA5
Overview:	A-1200 ; 0...40 bar gauge; one switching output (PNP) Accuracy: 1.0% of span Measuring range: 0...40 bar gauge Process connection: G1/4 A ISO1179-2 Sealing: NBR Permissible medium temperature: -30...+100°C Output signal: one switching output (PNP) IO-Link: IO-Link 1.1 Status Indication: Integrated indication Power supply: 10 ... 32 V DC Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1, U-=3, SP1/C=4 Overload Safety: 2 x Approvals: cULus Test protocol: with test protocol Type of packaging: single packaging Specifications according to data sheet: PE 81.90	
Details:	A-1200 ; 0...40 bar gauge; one switching output (PNP) Accuracy: 1.0% of span Measuring range: 0...40 bar gauge Process connection: G1/4 A ISO1179-2 Sealing: NBR Permissible medium temperature: -30...+100°C Output signal: one switching output (PNP) IO-Link: IO-Link 1.1 Status Indication: Integrated indication Power supply: 10 ... 32 V DC Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1, U-=3, SP1/C=4 Overload Safety: 2 x Approvals: cULus Test protocol: with test protocol Type of packaging: single packaging Specifications according to data sheet: PE 81.90	

© 2024 - WIKA Instruments s.a.r.l.