DATASHEET - TSQD1NO

Series connection time switch 24 hrs., segments, autonomy, 1 TLE

Part no.	**TSQD1NO**
	167388
EL Number (Norway)	**1456990**

General specifications

Product name	Eaton Distribution parts
Part no.	TSQD1NO
EAN	4015081638871
Product Length/Depth	65.5 millimetre
Product height	90 millimetre
Product width	17.5 millimetre
Product weight	0.08 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accuracy per day	1 s
Ambient operating temperature - max	50 °C
Ambient operating temperature - min	-10 °C
Autonomy in hours	72 h
Autonomy in years	0 a
Contact type	Normally open contact
Degree of protection	IP20
EL number	1456990
Equipment heat dissipation, current-dependent	0 W
Frequency supply voltage - max	60 Hz
Frequency supply voltage - min	45 Hz
Functions	Potential free switch contact Manual operation 24 h program Quartz controlled
Heat dissipation capacity	0 W
Heat dissipation per pole, current-dependent	0 W
Nominal switching current at 250 V AC	16 A
Number of channels	1
Program shift divide 1	15 min
Program shift divide 2	0 min
Rated operational current for specified heat dissipation (In)	0 A
Shortest switching time at channel 1	15 min
Shortest switching time at channel 2	0 min
Static heat dissipation, non-current-dependent	0.5 W
Supply voltage - max	240 V
Supply voltage - min	230 V
Switching power LED - max	600 W
Voltage type	AC/DC
Width in number of modular spacings	1

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Analogous time switch for distribution board (EC002304)

Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Analogous time switch (ecl@ss13-27-20-01-09 [ACN651016])			
Mounting method			DIN rail
Number of channels			1
Supply voltage		V	230 - 240
Voltage type (supply voltage)			AC/DC
Frequency supply voltage		Hz	45 - 60
Autonomy in hours			72
Autonomy in years			0
Accuracy per day		s	1
60 min program			No
24 h program			Yes
Weekly program			No
Annual program			No
Mains synchronous			No
Quartz controlled			Yes
Contact type			Normally open contact
Shortest switching time channel 1		min	15
Shortest switching time channel 2		min	0
Program shift divide 1		min	15
Program shift divide 2		min	0
Automatic switching summer-/winter time			No
Suitable for manual operation			Yes
Switching preselection			No
Nominal switching current at 250 V AC		A	16
Max. switching power LED		W	600
Potential free switch contact			Yes
Degree of protection (IP)			IP20
Width in number of modular spacings			1
Width		mm	17.5
Height		mm	90
Depth		mm	65.5

© 04/2023 by Eaton Industries GmbH