Specifications

Eaton 007466



Catalog Number: 007466

Eaton breaker. Copper busbar, 20x5x2250mm, tinned

General specifications

Product Name
Eaton xEffect SASY 60i copper busbar flat

Catalog Number
007466

EAN
4015080074663

Product Length/Depth
2250 mm

Product Height
5 mm

Product Width
20 mm

Product Weight
2.01 kg

Compliances
RoHS conform

Certifications
UL Listed
EN 13061

Powering Business Worldwide

Product specifications

Used with

SH0632
SH0635/4
System for flat busbars
60 mm system
Accessory panel building
Modular busbar system
General switchboard accessory

Special features

Flat copper busbars

Type

60 mm system
Accessory panel building
General switchboard accessory
Modular busbar system
System for flat busbars

Accessory/spare part type

Flat copper bars

Surface finishing

Tinned

Surface protection

Tinned

Unit type

Modular system

Ambient operating temperature - max

35 °C

Nominal current

250 A

Distance between busbar centers

60 mm

Functions

Flat busbar
Prepared enclosure
System for flat busbars

Rated operation current (Ie)

250 A

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Product Range Catalog Switching and protecting motors

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Drawings

eaton-control-panels-xeffect-sasy-busbar-3d-drawing.eps

Material

Copper, tinned

Model

Flat

Uninterrupted current (Iu) of bar

630 A (30 x 10 mm, Tu=35 °C and Ts=65 °C)

200 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

520 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)

320 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

360 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

450 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia