Date: 25/01/2024

612.20.100 0 mbar...40 mbar G1/2B lower back mount

612.20 100 Inox brut 40 mBar G

Item number: 9071784

Quantity: 1 pcs.

Order code: 612.20-E-MAEOZZ-GD-3ZZGZZZ-ZZZ V3AFZZ2FZZSAZMA DIAL-IAZ1ZZZZZZ1Z- ZZ3Z4ZZZZ LABEL-ASASZDE-

Overview:
612.20.100 0 mbar...40 mbar G1/2B lower back mount
Capsule pressure gauge, industrial series
class 1.6
Single packing
EN 837-3 *WIKA*
Cl.1.6

Details:
612.20 100 Inox brut 40 mBar G
MANOMETER 612.20 100 CrNi-Stahl blank 40 mBar G1/2B RUE

Druckmessgerät mit Kapselfeder, Robustausführung Typ: 612.20 Technische Daten nach Datenblatt: PM 06.02 Mess-System: Kupferlegierung Gehäuse: CrNi-Stahl Zeigerwerk: Kupferlegierung Ring: Bajonettring, CrNi-Stahl Genauigkeitsklasse: Kl. 1,6 Nenngröße: 100
Capsule pressure gauge, industrial series
Model: 612.20
Specifications according to data sheet: PM 06.02
Measuring system: copper alloy
Case: stainless steel
Movement: copper alloy
Bezel ring: cam ring (bayonet type), stainless steel
Nominal size: 100 mm
Unit: mbar
Scale range: 0 mbar...40 mbar
Process connection: G 1/2 B
Connector location: lower back mount
Case type: without blow-out disc on top
Accuracy class: class 1.6
Movement: copper alloy
Ingress protection: IP 54
Package: Single packing
Case: stainless steel
Pointer: standard, aluminium
Pointer colour: black
Window: flat instrument glass
Dial description:
Pressure Gauge Standard: International (standard Europe)

© 2024 - WIKA Instruments s.a.r.l.

color for 1.scale (outside): black
dial background: White
Manufacturer logo: *WIKA*
norm-mark on dial: *EN 837-3*
accuracy class on dial: *Cl.1.6*
inner packages label: Standard (with Wika Logo)
outside packages label: Standard (with Wika Logo)

© 2024 - WIKA Instruments s.a.r.l.