Specifications

Eaton 271461

Catalog Number: 271461

Eaton Moeller series NZM - Molded Case Circuit Breaker. Tunnel terminal, 3p, 1 page, max. 2x240mm², size 3



General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
271461

EAN
4015082714611

Product Length/Depth
92.5 mm

Product Height
102 mm

Product Width
137 mm

Product Weight
1.162 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
CSA (File No. 22086)
UL (Category Control Number DIHS)
IEC60947
CSA (Class No. 1432-01)
CE marking
UL (File No. E31593)
CSA-C22.2 No. 5-09
UL489
UL listed
CSA certified

Powering Business Worldwide

Product specifications

Used with

NZM3, PN3, N(S)3

Type

Accessory
Tunnel terminal

Amperage Rating

630 A (IEC), 550 A (UL/CSA)

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM3

Drawings

eaton-circuit-breaker-terminals-nzm-tunnel-terminal-dimensions-002.eps

eaton-general-nzm-tunnel-terminal-dimensions-002.eps

123I679

Installation instructions

eaton-circuit-breakers-nzm-2-3-(-4)-xka1-2-instruction-leaflet-il01210007z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CD-nzm3_xka2

DA-CS-nzm3_xka2

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM3

Suitable for

Copper cable

Three-pole

Number of poles

Three-pole

Model

Other

Terminal capacity (stranded cable)

50 mm² - 240 mm² (2x) at digital input of supply connection

Max. 500 AWG/kcmil (2x)

Max. 500 AWG/kcmil (1x)

50 mm² - 240 mm² (1x) at digital input of supply connection



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia