Specifications

Eaton 2D16



Catalog Number: 2D16

Eaton Bussmann series low voltage D fuse, 500V, 2A, 50 kAIC, Non Indicating, fuse, Class C gL/gG, Time delay, Holder, Pink, Ceramic body

General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
2D16

EAN
5027590472432

UPC
051712833431

Product Length/Depth
50 mm

Product Height
13.2 mm

Product Width
13.2 mm

Product Weight
11 g

Compliances
GoST-R
CE Marked
RoHS Compliant

Certifications
IEC 60269
VDE
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

fuse

Application

For domestic and general industrial applications

Amperage Rating

2 A

Fuse size

DI

Breaking capacity

50 kA

Construction size (fuse inserts)

DI

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

D16 - Time delay

Accessory/spare part type

2GD16 Pink screw cap gauge piece

Utilization category

gL/gG (cable protection/equipment protection)

Color

Pink

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D1

Construction size

DI

Fuse shape

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

UKCA Bottle fuse-links, holders, carriers and accessories

CE Bottle fuse-links, holders, carriers and accessories

Technical data sheets

4124 D and D0 fuses, bases and accessories

Bottle

Response time

Time-delay

Suitable for

E16/DI Fuse base

Material

White ceramic body

Mounting method

Holder

Release characteristic

Time-lag

Quantity

20

Voltage rating

500 V

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia