


ARCALUB-X.CHAIN-PINION-10AB2-Z10-W

Chain lubrication pinion

Chain lubrication pinion duplex, Lubricant feed radial

Technical information



Your current product variant

Version	AB-/B-2	Chain lubrication pinions, duplex design

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website

Technical data

	Lubrication of chains	Usage
	Duplex (double-row)	Design
	radial	Lubricant feed
	Pinion: plastic, roller: open cell PU foam	Material
t_{op}	0 °C … +60 °C	Operating temperature
	7 m/s	Max. permissible circumferential speed at outside diameter
	Oil	Lubricant
	10 A/B-2	Chain type according to ISO 606
z	10	Teeth number
d	51.37 mm	Pitch circle diameter
d_a	55 mm	
d_b	39 mm	
B_1	29 mm	
B_2	5 mm	
B_3	15 mm	
L_1	31.2 mm	
L_2	45.7 mm	
L_3	61.4 mm	
W	24 mm	Width across flats
≈m	0.4 kg	Weight

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website