*Date: 11/04/2023*

# PSD-4-ECO ; 0...25 bar gauge; one switching output (PNP) + 4...20 mA

## PSD-4-ECO ; 0...25 bar gauge; one switching output (PNP) + 4...20 mA

| | |
|---|---|
| Item number: | 48784484 |
| Quantity: | 1 pcs. |
| Order code: | PSD-4-ECO-D-BG425-013Z-2O1CZZS-ULZZ-GSFJ W1011P4E-ZZOSW- |
| Overview: | PSD-4-ECO ; 0...25 bar gauge; one switching output (PNP) + 4...20 mA<br>OEM Pressure Switch with Display<br>Output signal: one switching output (PNP) + 4...20 mA<br>IO-Link: without<br>Power supply: 15 ... 32 V DC<br>Measuring range: 0...25 bar gauge<br>Process connection: G1/4 B EN 837<br>Sealing: without<br>Permissible medium temperature: -25...+85°C<br>Electrical connection: circular connector M12x1, 4-pin<br>pin assignment: U+=1,S+=2, U-=3, SP1 =4<br>Overload Safety: 2 x<br>Accuracy: 1.0% of span<br>Approvals: cULus<br>Type of packaging: single packaging<br>Specifications according to data sheet: PE 81.69 |
| Details: | PSD-4-ECO ; 0...25 bar gauge; one switching output (PNP) + 4...20 mA<br>OEM Pressure Switch with Display<br>Output signal: one switching output (PNP) + 4...20 mA<br>IO-Link: without<br>Power supply: 15 ... 32 V DC<br>Measuring range: 0...25 bar gauge<br>Process connection: G1/4 B EN 837<br>Sealing: without<br>Permissible medium temperature: -25...+85°C<br>Electrical connection: circular connector M12x1, 4-pin<br>pin assignment: U+=1,S+=2, U-=3, SP1 =4<br>Overload Safety: 2 x<br>Accuracy: 1.0% of span<br>Approvals: cULus<br>Type of packaging: single packaging<br>Specifications according to data sheet: PE 81.69 |

*© 2023 - WIKA Instruments s.a.r.l.*