Specifications

Eaton 084350



Catalog Number: 084350

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, 1600A, for copper band, PEN

General specifications

Product Name
Eaton xEnergy Safety Ci busbar enclosure accessory

Catalog Number
084350

EAN
4015080843504

Product Length/Depth
40 mm

Product Height
30 mm

Product Width
40 mm

Product Weight
0.301 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Used with

Cu 1 x (30 mm x 10 mm) busbars
Ci insulated enclosure
Prepared enclosures
Accessory for busbar enclosures

Special features

For protective or neutral conductor PE, N, PEN

Type

Accessory for busbar enclosures
Ci insulated enclosure
Prepared enclosures

Accessory/spare part type

Busbar terminals

Width clamp

17 mm

Busbar thickness - max

10 mm

Busbar thickness - min

10 mm

Busbar width - max

60 mm

Busbar width - min

30 mm

Conductor cross section - max

1000 mm²

Rated operational current (Ie) - max

1600 A

Functions

Connection for flat cable and cu bar

Suitable for

Flat rail
Strip conductor connection

Rated operational current

1600 A

Terminal capacity (flat strip)

Resources

Brochures

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-insulated-boards-busbar-xenergy-safety-ci-busbar-terminal-3d-drawing-004.eps

50 mm x 12 mm

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia