DATASHEET - IZMX-CS40-1

Signalling switch, circuit-breaker position, 1W, right or left

Part no.	**IZMX-CS40-1**
	184196
EL Number (Norway)	**4398539**

General specifications			
Product name			Eaton Moeller series IZMX/INX auxiliary contact block
Part no.			IZMX-CS40-1
EAN			4015081783625
Product Length/Depth			125 millimetre
Product height			100 millimetre
Product width			10 millimetre
Product weight			0.1 kilogram
Compliances			RoHS conform
Product Tradename			IZMX/INX
Product Type			Accessories
Product Sub Type			Auxiliary contact block
Delivery program			
Type			Accessory
Model			Integrable
Special features			The retrofit kit includes the required SEC control cable terminals. for fitting to left or right One changeover contact each for the Disconnected, Test, and Connected positions.
Used with			IZMX-CAS40…
Technical Data - Electrical			
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V			10 A
Rated breaking capacity (inductive load)			10 A (250 V AC) 0.25 A (250 V DC) 0.5 A (125 V DC)
Electric connection type			Flat plug-in connection
Technical Data - Mechanical			
Mounting Method			Floor fastening Withdrawable
Number of contacts (change-over contacts)			1
Number of contacts (normally closed contacts)			2
Number of contacts (normally open contacts)			2
Number of switches (fault signal)			0
Lamp holder			None
Design verification as per IEC/EN 61439 - technical data			
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Additional information			
Accessory/spare part type			Withdrawable units

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])

Number of contacts as change-over contact			1
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Number of fault-signal switches			0
Rated operation current Ie at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection

Model			Integrable
Mounting method			Floor fastening
Lamp holder			None

© 04/2023 by Eaton Industries GmbH