
OGH309

Diffuse reflection sensor with background suppression

OGH-DPKG/6M



Product characteristics		
Type of light		red light
Housing		threaded type
Application		
Special feature		Background suppression
Function principle		Diffuse reflection sensor
Electrical data		
Operating voltage	[V]	10...36 DC
Current consumption	[mA]	25
Protection class		II
Reverse polarity protection		yes
Type of light		red light
Outputs		
Electrical design		PNP
Output function		dark-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	150; (200 (...60 °C))
Switching frequency DC	[Hz]	1000
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes
Detection zone		
Range	[mm]	< 200; (white paper 200 x 200 mm 90% remission)
Range on white object (90 % remission)	[mm]	< 200
Range on grey object (18 % remission)	[mm]	< 200
Range on black object (6 % remission)	[mm]	< 190

OGH309


Diffuse reflection sensor with background suppression

OGH-DPKG/6M

Range adjustable			no
Max. light spot diameter	[mm]		17
Light spot dimensions refer to			Range
Background suppression available			yes
Operating conditions			
Ambient temperature	[°C]		-25...80
Protection			IP 65; IP 67; IP 68; IP 69K
Tests / approvals			
EMC		EN 60947-5-2	
MTTF	[years]		372
Mechanical data			
Weight	[g]		256.5
Housing			threaded type
Dimensions	[mm]		M18 x 1 / L = 80.4
Thread designation			M18 x 1
Materials			housing: stainless steel (316L/1.4404); Sealing: EPDM
Lens material			PMMA
Displays / operating elements			
Display		switching status	1 x LED, yellow
Accessories			
Items supplied			lock nuts: 2
Remarks			
Remarks			operating voltage "supply class 2" according to cULus
Pack quantity			1 pcs.
Electrical connection			

Cable: 6 m, PVC; 3 x 0.34 mm²

Connection



	Core colours :
BK =	black
BN =	brown
BU =	blue