Specifications

Eaton 135920



Catalog Number: 135920

Eaton Moeller® series E57 Proximity switch, E57 Global Series, 1 N/O, 2-wire, 10 - 30 V DC, M18 x 1 mm, Sn= 16 mm, Non-flush, NPN/PNP, Metal, Plug-in connection M12 x 1

General specifications

Product Name
Eaton Moeller® series E57 Proximity switch

Catalog Number
135920

EAN
4015081327133

Product Length/Depth
114.3 mm

Product Height
12.7 mm

Product Width
25.4 mm

Product Weight
0.09 kg

Certifications
UL File No.: CSA report applies to both US and Canada
CSA
CSA Class No.: 4652-04 / 4652-84
CSA-C22.2 No. 14
UL 508
CSA File No.: 224447
CE
IEC/EN 60947-5-2

Powering Business Worldwide

Product specifications

Type
Inductive sensor

Electric connection type
Connector M12

Enclosure material finishing
Other

Actuation type
Metallic Target

Enclosure material
Metal

Enclosure type
Cylinder, screw-thread

Category (EN 954-1)
B

Explosion safety category for dust
None

Explosion safety category for gas
None

Safety performance level (EN ISO 13849-1)
None

SIL (IEC 61508)
None

Ambient operating temperature - max
60 °C

Ambient operating temperature - min
0 °C

Diameter sensor
18 mm

Number of contact energized outputs with signalling function
0

Number of contacts (normally open contacts)
1

Number of outputs (protected contact energized)
0

Number of outputs (protected semiconductor)

Resources

Brochures
eaton-sensors-brochure-br053001en-en-us.pdf

Catalogs
Product Range Catalog Sensors – products, basic information, applications

Declarations of conformity
DA-DC-00004651.pdf

DA-DC-00004656.pdf

Drawings
1360DIM-56

eaton-proximity-switches-e57-proximity-switch-3d-drawing-002.eps

eCAD model
DA-CE-ETN.E57-18GE16-DDB

Installation instructions
IL05301002Z

Multimedia
We make what matters

0

Number of outputs (semiconductor with signaling function)

1

Operational current (Ib) in the switched state at 24 V DC

10 A

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Voltage type

DC

Mounting method

Non-flush mounting

Material

Metal

Connection type

2-wire

Plug-in connection M12 x 1

Installation type

Not flat

Degree of protection

IP67

IP69

NEMA Other

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Normally open contact

Load current

3 - 100 mA (Ie)

Residual current

0.8 mA (through the load in the blocked state at 230 V AC and 24 V DC)

Residual ripple

10 % (U_e)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

500 Hz

Voltage rating - max

30 V

Width sensor

0 mm

Product category

E57 Global Series

Switching output type

PNP/NPN

Temperature drift of sn

10 %

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

30 V

Rated control supply voltage (Us) at DC - min

10 V

Rated switching distance (Sn) - max

16 mm

Repeatability

2 %

Sensor height

0 mm

Sensor length

79 mm

Supply voltage - max

30 V

Supply voltage - min

10 V

Switching hysteresis of Sn

15 %

Voltage drop (Ud)

6 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia