DATASHEET - XV-303-10-B02-A00-1B

User interface, 24VDC, 10.1-inch PCT display,1024x600 pixels,1xEthernet,1xRS232,1xRS485, 1xCAN, 1xProfibus, 1xSD card slot, PLC function can be added

Powering Business Worldwide

Part no.	**XV-303-10-B02-A00-1B**
	179663
EL Number (Norway)	**4501306**

Product name	Eaton XV-303 Touch panel
Part no.	XV-303-10-B02-A00-1B
EAN	7640130098565
Product Length/Depth	269 millimetre
Product height	58 millimetre
Product width	174 millimetre
Product weight	1.195 kilogram
Certifications	UL CE DNV GL CUL EN 50178 UL File No.: E205091 EMC according to 2014/30/EU Certified by UL for use in Canada UL 61010-2-201 IEC/EN 61131-2
Product Tradename	XV-303
Product Type	Touch panel
Product Sub Type	None
Catalog Notes	12 W for basic device + 2.5 W for USB module Can be fitted by user with article no. 181585 LIC-PLC-A Heat dissipation with power consumption for 24 V License certificates for onboard interfaces not required Optionally with SD card -> article no. 181638
Enclosure material	Insulated material
Features	RS232 USB Host Integrated Runtime visualization software license RS485 Fanless CPU and system cooling, natural convection-based passive cooling Slot for SD card USB device Operating System Windows Embedded Compact 7 pro Ethernet interface Target and web visualization Portrait format CAN
Fitted with:	MPI interface SW interfaces 1 x Ethernet 10/100 Mbps (built-in interfaces) 1 x CANopen®/easyNet (built-in interfaces) Message system (incl. buffer and confirmation) Color display 1 x PROFIBUS/MPI (built-in interface) Printer output 1 x RS485 (built-in interface) 1 x USB device (built-in interface) 1 x RS232 (built-in interface) 1 x USB host 2.0 (built-in interface) Message indication Recipes
Functions	Process value representation (output) possible Process default value (input) possible Additional software components, loadable
Battery runtime	Back-up of real-time clock: BR 2330, non-replaceable (soldered)
Degree of protection	IP20, rear (according to EN 60529-1) NEMA 12 NEMA 4X
Degree of protection (front side)	IP65 NEMA 12

Fuse type	Built-in fuse (not accessible)
Lifespan	50,000 h (Service life of back-lighting)
Model	Plastic enclosure and glass panel in plastic frame
Mounting method	Flush mounting - Inclination from vertical: ±45° (if using natural convection) Flush mounting - Clearance: Width x Height x Depth ≥ 30 mm (1.18") Flush mounting
Potential isolation	Power supply: no
Protection against polarity reversal	Yes, for supply voltage (Siemens MPI optional)
Product category	HMI-PLC (SPS function, retrofittable)
RoHs conformity	Yes
Software	XSOFT-CODESYS, Visualisation software, Engineering GALILEO, Visualisation software, Engineering XSOFT-CODESYS-3, PLC-Programming software, Engineering XSOFT-CODESYS-2, PLC-Programming software, Engineering
Type	Control panel with Profibus
Voltage type	DC
Shock resistance	15 g, 11 ms, Mechanical
Vibration resistance	60 - 150 Hz, ± 2 g 9 - 60 Hz, ± 0.15 mm 5 - 9 Hz, ± 3.5 mm
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	0 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-20 °C
Ambient storage temperature - max	60 °C
Climatic proofing	Dry heat to IEC 60068-2-2 Cold to EN 60068-2-1 Damp heat, constant, to IEC 60068-2-3
Environmental conditions	Condensation: Non-condensing
Operating temperature - min	0 °C
Operating temperature - max	50 °C
Relative humidity	10 - 95 % (non-condensing)
Emitted interference	According to IEC/EN 61000-6-4
Interference immunity	According to EN 61000-6-2
Voltage dips	5 ms from undervoltage (19.2 V DC) ≤ 10 ms from rated voltage (24 V DC)
Permissible voltage	19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %) 18.0 - 31.2 V DC, absolute with ripple 35 V DC (for a duration of < 100 ms) 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %)
Power consumption	18 W typ. Max. 18 W
Rated operational voltage	24 V DC (power-supply - safety extra low voltage)
Supply voltage at AC, 50 Hz - min	0 V AC
Supply voltage at AC, 50 Hz - max	0 V AC
Supply voltage at DC - min	19.2 V DC
Supply voltage at DC - max	30 V DC
Communication interface	PROFIBUS-DP, not galvanically isolated, 9 pole SUB-D socket, UNC
Interfaces	CAN (not galvanically isolated, 9-pin SUB-D plug, UNC) 10/100 Mbps Ethernet connection USB 2.0 device (not galvanically isolated) RS232 (not galvanically isolated, 9-pin SUB-D plug, UNC) USB 2.0 host (not galvanically isolated) RS485 (not galvanically isolated, 9-pin SUB-D plug, UNC)
Number of slots	1 (for SD-Card)
Protocol	EtherNet/IP PROFIBUS TCP/IP CAN MODBUS

Display contrast ratio	500:1
Display lighting	Dimmable via software LED
Display size	222.72 x 125.28 mm 16:9
Display type	Color display, TFT, anti-glare TFT Anti-glare tempered glass in plastic bezel
Luminance intensity	400 cd/m²
Number of colors of the display	16777216
Resolution	1024 x 600 px WSVGA
Screen size (diagonal)	10.1 in
Touch technology	Projected Capacitive Touch (PCT) Multi-touch touch panel touch sensor Capacitive multitouch
Backup time	10 years, typ. (time at zero voltage)
Memory	DRAM: 512 MByte RAM Flash: 1 GByte SLC SD card, Type: SDSC, SDHC (external memory) NVRAM: 128kByte Retain
Memory capacity	512,000 kByte
Operating system	Windows Embedded Compact 7 Pro
Processor	ARM Cortex-A9 800 MHz
Equipment heat dissipation, current-dependent Pvid	18 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	18 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Graphic panel (EC001412)

Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Graphic panel (HMI) (ecl@ss10.0.1-27-33-02-01 [AFX016003])

Supply voltage AC 50 Hz	V	0 - 0

Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	19.2 - 30
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		1
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		1
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		2
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		2
With SW interfaces		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Type of display		TFT
With colour display		Yes
Number of colours of the display		16,777,216
Number of grey-scales/blue-scales of display		0
Screen diagonal	inch	10.1
Number of pixels, horizontal		1,024
Number of pixels, vertical		600
Useful project memory/user memory	kByte	512,000
With numeric keyboard		No
With alpha numeric keyboard		No
Number of function buttons, programmable		0
Number of buttons with LED		0
Number of system buttons		1

Touch technology			Capacitive multitouch
With message indication			Yes
With message system (incl. buffer and confirmation)			Yes
Process value representation (output) possible			Yes
Process default value (input) possible			Yes
With recipes			Yes
Number of password levels			200
With printer output			Yes
Number of online languages			100
Additional software components, loadable			Yes
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			12
Operating temperature		°C	0 - 50
Rail mounting possible			No
Wall mounting/direct mounting			No
Suitable for safety functions			No
Width of the front		mm	269
Height of the front		mm	174
Built-in depth		mm	50.1

© 04/2023 by Eaton Industries GmbH