DATASHEET - NZMN2-4-AF100-BT-NA

Circuit-breaker, 4p, 100A, box terminals

Part no. **NZMN2-4-AF100-BT-NA**
153390

General specifications

Product name	Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no.	NZMN2-4-AF100-BT-NA
EAN	4015081501601
Product Length/Depth	149 millimetre
Product height	206 millimetre
Product width	140 millimetre
Product weight	3.755 kilogram
Compliances	RoHS conform
Certifications	UL (Category Control Number DIVQ) IEC/EN 60947 IEC UL listed CE marking UL (File No. E31593) UL 489 IEC 60947-2 Specially designed for North America UL/CSA CSA-C22.2 No. 5-09
Product Tradename	NZM
Product Type	Molded case circuit breaker
Product Sub Type	Thermo-magnetic

Delivery program

Application	Use in unearthed supply systems at 690 V Branch circuits, feeder circuits
Type	Circuit breaker
Circuit breaker frame type	NZM2
Number of poles	Four-pole
Amperage Rating	100 A
Release system	Thermomagnetic release
Features	Protection unit Motor drive optional
Special features	Fixed overload releases Ir Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Rated current = rated uninterrupted current: 100 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)

Technical Data - Electrical

Voltage rating	690 V - 690 V
Rated operating voltage Ue (UL) - max	480 V
Rated insulation voltage (Ui)	1000 V AC
Rated impulse withstand voltage (Uimp) at auxiliary contacts	6000 V
Rated impulse withstand voltage (Uimp) at main contacts	8000 V
Current rating of neutral conductor	200% of phase conductor
Rated operational current	100 A (690 V AC-1, making and breaking capacity)
Rated short-time withstand current (t = 0.3 s)	1.9 kA
Rated short-time withstand current (t = 1 s)	1.9 kA
Instantaneous current setting (Ii) - min	6 A
Instantaneous current setting (Ii) - max	10 A
Overload current setting (Ir)	100 A - 100 A
Overload current setting (Ir) - min	100 A
Overload current setting (Ir) - max	100 A
Short delay current setting (Isd) - min	0 A

Short delay current setting (Isd) - max	0 A
Short-circuit release non-delayed setting - min	600 A
Short-circuit release non-delayed setting - max	1000 A
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz	85 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz	50 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz	35 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz	25 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz	5 kA
Rated short-circuit making capacity Icm at 240 V, 50/60 Hz	187 kA
Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz	105 kA
Rated short-circuit making capacity Icm at 440 V, 50/60 Hz	74 kA
Rated short-circuit making capacity Icm at 525 V, 50/60 Hz	53 kA
Rated short-circuit making capacity Icm at 690 V, 50/60 Hz	40 kA
Short-circuit total breaktime	< 10 ms
Low-voltage HBC fuse - max	355 A gG/gL
Electrical connection type of main circuit	Frame clamp
Isolation	300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max	120
Handle type	Rocker lever
Utilization category	A (IEC/EN 60947-2)
Overvoltage category	III
Pollution degree	3
Lifespan, electrical	7500 operations at 690 V AC-1 5000 operations at 690 V AC-3 10000 operations at 400 V AC-1 6500 operations at 400 V AC-3
Direction of incoming supply	As required

Technical Data - Mechanical

Mounting Method	Fixed Built-in device fixed built-in technique DIN rail (top hat rail) mounting optional
Degree of protection	IP20 (basic degree of protection, in the operating controls area) IP20
Degree of protection (IP), front side	IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)	IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
Protection against direct contact	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance	20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)	0
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0
Position of connection for main current circuit	Front side
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Special features	Fixed overload releases Ir Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate. Rated current = rated uninterrupted current: 100 A Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Lifespan, mechanical	20000 operations

Technical Data - Mechanical - Terminals

Standard terminals	Box terminal
Terminal capacity (aluminum solid conductor/cable)	16 mm^2 (1x) at tunnel terminal

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)	100 A
Equipment heat dissipation, current-dependent	25.65 W
Ambient operating temperature - min	-25 °C

Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		System and cable protection Current limiting circuit breaker

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])

Rated permanent current Iu	A	100
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA	50
Overload release current setting	A	100 - 100
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	6 - 10
Power loss	W	
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Frame clamp
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		Yes
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		4
Position of connection for main current circuit		Front side
Type of control element		Rocker lever

Complete device with protection unit			Yes
Motor drive integrated			No
Motor drive optional			Yes
Degree of protection (IP)			IP20

© 04/2023 by Eaton Industries GmbH