CAT. N° 4 105 00



ADD-ON MODULES DX³ - 4P 400 V~ - 63 A - 30 MA - AC TYPE - FOR 1 MODULE DX³ MCB

Pack (number of units)	1
Volume (dm³)	1,684
Weight (g)	364,00

Product characteristics

4-pole - 400 V~

AC Type

- Sensitivity : 30 mA
- Nominal rating In : 63 A
- Number of modules : 3

General characteristics

Add-on modules DX³ - for 1 module/pole DX³ MCBs

- Conform to IEC 61009-1, IEC 62423 (F type)
- Voltage independent tripping except Cat.No 4 106 57/58/59
- AC type : detect AC components faults
- A type : detect AC and DC component faults
- F type (High immunity) : detect faults with AC and DC components, increased immunity to false tripping
- Detection of high frequency fault currents
- For mounting on the right-hand side of 1 module per pole DX³ MCBs

Documentation

Catalogue pages & additional information

- Description page (p.070)
- Technical page (p.071)
- Dimensions of din-rail equipment
- Performance of MCBs and auxiliaries

Installation & technical data

- F01305EN-05

Environmental product profile

- Environnemental product sheet n°20 E0113A-FR
- LGRP-00816-V01

Installation instructions & related documents

- G8191D

Agreements & certificates of conformity

- NF-NF012_1340
- OC / CB-IT-11142

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.