Date: 24/04/2023

232.50.063 6 bar Diaphragm Seal lower mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number: 48708548

Quantity: 1 pcs.

Order code: DSS1-MT990.31-123X50-DZZZD-C8C65ZE1-ZZAZZZZZ WAZ-Z
LABEL-PG1DE-ZZZZZ- ZZZZZ
232.50-C-BG360Z-CA-UZEZKZZ-ZZZZZZZ 313D41ZIXX0 Z2Z-
IZZZZZZ121Z#
H990.31G2FPPPTPD

Overview: 232.50.063 6 bar Diaphragm Seal lower mount
Measuring System 316 SS
Ingress protection: IP 65
class 1.6
Window: polycarbonate
adjustable knife-edge pointer, aluminium, black
Pressure Gauge Standard: International (standard Europe)
stop-pin at zero *WIKA*
with Serial number
individual text for dial: Special scale interval all the 0,1 bar

Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 21 Halocarbon oil (6.3)(see IN 00.06)
Process temperature min.: 0°C
Process temperature max.: + 60°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C

990.31 G 1/2" female
Upper body material / main body material: PP blue RAL 5002
Diaphragm material: PTFE
Lower part material: PVDF white, translucent

Label: WIKA standard without / with Tag-number

Details: Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 232.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: without
Nominal size: 063 mm

© 2023 - WIKA Instruments s.a.r.l.

Scale range: 0...6 bar
Process connection: Diaphragm Seal
Connector location: lower mount
Window: polycarbonate
Pointer: adjustable knife-edge pointer, aluminium, black
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: prepared for filling
Ingress protection: IP 65
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
individual text for dial: Special scale interval all the 0,1 bar
stop pin on dial: at zero
Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 21 Halocarbon oil (6.3)(see IN 00.06)
Process temperature min.: 0°C
Process temperature max.: + 60°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Diaphragm seal, plastic body
Specifications according to data sheet: DS 99.02
Effective diaphragm diameter: 43 mm
Specifications according to data sheet: Pressure-temperature-rating according to datasheet
Diaphragm seal: Model 990.31
Threaded connection: G 1/2" female
Upper body material / main body material: PP blue RAL 5002
Diaphragm material: PTFE
Lower part material: PVDF white, translucent

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.