Date: 13/04/2023

RLS-5000; 1 switching output (changeover / SPDT); 8 m

RLS-5000; 1 switching output (changeover / SPDT); 8 m

Item number: 14247860

Quantity: 1 pcs.

Order code: RLS-5000-9-DNM0008-1-GZ W101ARS5ZL8

Overview:
RLS-5000; 1 switching output (changeover / SPDT); 8 m
Bilge float switch, For the shipbuilding industry Model RLS-5000 (model with approval: SR 6)
Output Signal: 1 switching output (changeover / SPDT)
max. switching power: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Electrical connection: flying lead, IP 68
Cable length: 8 m
pin assignment el. connection: SP= bk/bn, bn/gy
Test function : with
Permissible temperature range medium: -40 … 80 °C
Wetted parts: Stainless steel 1.4571, Polyolefin
Approvals: GL,LR
Specifications according to data sheet: LM 50.08

Details:
RLS-5000; 1 switching output (changeover / SPDT); 8 m
Bilge float switch, For the shipbuilding industry Model RLS-5000 (model with approval: SR 6)
Output Signal: 1 switching output (changeover / SPDT)
max. switching power: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Electrical connection: flying lead, IP 68
Cable length: 8 m
pin assignment el. connection: SP= bk/bn, bn/gy
Test function : with
Permissible temperature range medium: -40 … 80 °C
Wetted parts: Stainless steel 1.4571, Polyolefin
Approvals: GL,LR
Specifications according to data sheet: LM 50.08

© 2023 - WIKA Instruments s.a.r.l.