Rittal – The System.

Faster – better – everywhere.

Baying enclosure system VX25, stainless steel IP 66/NEMA 4X – VX 8458.000

Date : Apr 27, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying enclosure system VX25, stainless steel IP 66/NEMA 4X – VX 8458.000

created: 27.04.2021 build on www.rittal.com/uk-en



Product description

Material:	Enclosure frame: Stainless steel 1.4301 (AISI 304), 1.5 mm Roof: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Gland plate: Stainless steel 1.4301 (AISI 304), 1.5 mm Mounting plate: Sheet steel, 3.0 mm
Surface finish:	Enclosure frame and gland plates: Uncoated Door, roof and rear panel: Exterior brushed, grain size 400 Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 1, 3R, 4, 4X, 12
Type rating to UL 50E:	Type 1, 3R, 4, 4X, 12
IK Code:	IK10
Supply includes:	Enclosure frame Door Door hinged on the right, may be swapped to the left Roof Base Rear panel Mounting plate Lock: 3 mm double-bit 2 punched rails 18 x 39 mm
Note:	Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation.

Basic material:	Stainless steel

Product description

Dimensions:	Width: 800 mm Height: 2000 mm Depth: 600 mm
Mounting plate:	Width: 699 mm Height: 1896 mm
Number of doors:	1
Packs of:	1 pc(s).
Weight/pack:	129 kg
EAN:	4028177924482
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	VX Baying enclosure system IP66 / NEMA4x, WHD: 800x2000x600 mm, stainless steel, 1.4301, with mounting plate, sheet steel, zinc-plaed, single door at the front

Approvals

Approvals:	UL + C-UL
Certificates:	NA
Declarations:	Declaration of conformity