DC 3-/4-wire Inductive Tubular Sensors
Tubular housing, M8×1







M8 × 1	**M8 × 1**	**M8 × 1**	**M8 × 1**	**M8 × 1**
Flush	Flush	Flush	Flush	Flush
2 mm	**2 mm**	**2 mm**	**2 mm**	**2 mm**
0...1.6 mm	0...1.4 mm	0...1.6 mm	0...1.4 mm	0...1.6 mm
2X	2X	2X	2X	2X
BES0148	**BES0149**	**BES00P7**	**BES02P0**	**BES01AU**
BES M08EE-PSC20B-S04G	BES M08EE-PSC20B-S04G-101	BES 516-324-G-E5-C-S49	BES 516-324-SA96-G-E5-C-S49	BES 516-324-G-S49-C
BES0144		**BES0113**		**BES01LP**
BES M08EE-POC20B-S04G		BES 516-377-G-E5-C-S49		BES 516-377-G-S49-C
BES0140		**BES00TY**	**BES02P1**	
BES M08EE-NSC20B-S04G		BES 516-343-G-E5-C-S49	BES 516-343-SA96-G-E5-C-S49	
BES013U		**BES0118**		
BES M08EE-NOC20B-S04G		BES 516-378-G-E5-C-S49		
10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC
2.5 V	2.5 V	2.5 V	2.5 V	2.5 V
250 V AC (⧈)	250 V AC (⧈)	250 V AC (⧈)	250 V AC (⧈)	250 V AC (⧈)
200 mA	200 mA	200 mA	200 mA	200 mA
Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes
–25...+70°C	–25...+70°C	–25...+70°C	–25...+70°C	–25...+70°C
1.5 kHz	1.5 kHz	1.5 kHz	1.5 kHz	1.5 kHz
Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED
IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20
CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus
Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
PBT	With ceramic coating	PBT	with ceramic coating	PBT
M12 connector, 4-pin	M12 connector, 4-pin	M8 connector, 3-pin	M8 connector, 3-pin	M8 connector, 3-pin
BCC M415-0000-1A-003-EX44T2-020	BCC M415-0000-1A-003-EX44T2-020	BCC M313-0000-10-001-EX43T2-020	BCC M313-0000-10-001-EX43T2-020	BCC M313-0000-10-001-EX43T2-020









