Ex enclosures Stainless steel, empty enclosure with hinged door – KEL 9404.600



Product description

Applications:	• Zone 1 and 2 or 21 and 22 to 94/9/EC • Ambient temperature range: -30°C...+80°C • Protection type to EN 60 079: Equipment protection thanks to increased safety, equipment protection thanks to enclosure
Material:	• Enclosure: Stainless steel 1.4301 (AISI 304) • Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal • Mounting plate: Sheet steel
Surface finish:	• Enclosure: Brushed, grain 240 • Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	• IP 66
Certificates:	• IEC Ex PTB 09.0035U: yes • PTB 02 ATEX 1082U: yes
Supply includes:	• Enclosure • Door • Mounting plate
Packs of:	• 1 pc(s).
EAN:	• 4028177138773

© Rittal 2013

Customs tariff number:	• 94032080

Product features

Dimensions:	• Width: 380 mm • Height: 600 mm • Depth: 210 mm
Mounting plate:	• Width: 334 mm • Height: 570 mm
Number of cam locks:	• 2
Weight:	• 13.3 kg

Approvals

Certificates:	• Ex (EN) • Ex (DE)
Declarations:	• Manufacturer's declaration (EN, DE)

Downloads

Documentation:	• Instructions (EN, DE)

© Rittal 2013