Date: 11/04/2023

60-ARV2"-VU-L240/12-V44A-Ex

60-ARV2"-VU-L240/12-V44A-Ex

Item number: 48687435

Quantity: 1 pcs.

Order code: FLS-CBMFZ007000884DA2ZZGFZZ0195UZZZZZZZZZZZZZZZZZZ
KBRVJA02401NZZZZ

Overview:
60-ARV2"-VU-L240/12-V44A-Ex
Float Switch Type FLS-SBI
Approval: ATEX Ex i; KEMA 01ATEX1053 X II 1/2G Ex ia IIC T6...T1 Ga/Gb - II 2 D Ex ib IIIC T80°C...T230°C Db
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 7.0 bar
Temperature range: -20°C up to 80°C
Fluid density: 884 kg/m³
Housing: Aluminium
Ingress protection: IP66/68
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Change-over (SPDT) 195 mm
Switch rating: Ui ≤ 36 V, Ii ≤ 100 mA, Pi ≤ 0,84W, Ci = 0 nF, Li = 0 µH
Float: Stainless steel 316Ti V44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 240 mm
Float stop: Float collar
Float fits through the connection nozzle
Weight: 1.2 kg

Details:
60-ARV2"-VU-L240/12-V44A-Ex
Float Switch Type FLS-SBI
Approval: ATEX Ex i; KEMA 01ATEX1053 X II 1/2G Ex ia IIC T6...T1 Ga/Gb - II 2 D Ex ib IIIC T80°C...T230°C Db
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 7.0 bar
Temperature range: -20°C up to 80°C
Fluid density: 884 kg/m³
Housing: Aluminium
Ingress protection: IP66/68
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Change-over (SPDT) 195 mm
Switch rating: Ui ≤ 36 V, Ii ≤ 100 mA, Pi ≤ 0,84W, Ci = 0 nF, Li = 0 µH
Float: Stainless steel 316Ti V44A; Float outer diameter: 44 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 240 mm

© 2023 - WIKA Instruments s.a.r.l.

Float stop: Float collar
Float fits through the connection nozzle
Weight: 1.2 kg

© 2023 - WIKA Instruments s.a.r.l.