SCHMERSAL
THE DNA OF SAFETY



T2FH232-11/11

- **Metal enclosure**
- **double-pedal type**
- **2 contacts per pedal**
- **High level of stability**
- **2 cable entries M 25 x 1.5**
- **Low operating height of pedal**
- **Protective shield with wide opening**

Data

Certifications	
Certificates	cULus CCC EAC
General data	
Product name	2F 232
Standards	EN 60947-5-1 DIN VDE 0660-200 BG-GS-ET-15
Enclosure material	Aluminium
Enclosure coating material	powder-coated
Material of the cover	Aluminium
Material of the pedal	Glass-fibre, reinforced thermoplastic
Material of the protective shield	Aluminium
Colour of the housing	RAL 9006 (White aluminum)
Gross weight	2990.000 g
General data - Features	
Protective shield	Yes
Probing possible	Yes
Number of pedals, NC	1
Number of pedals, NO	1
Mechanical data	
Mechanical life, minimum	1,000,000 Operations

Mechanical data - Connection technique	
Terminal Connector	Screw connection
Cable section, maximum	1 x 2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions	
Width	295 mm
Height	189 mm
Depth	274 mm

Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C

Ambient conditions - Insulation value	
Rated impulse withstand voltage	6 kV

Electrical data	
Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Slow action

Pictures


Product picture (catalogue individual photo)



ID: ktfh2f01

| 28,4 kB | .png | 74.083 x 59.972 mm - 210 x 170 Pixel - 72 dpi
| 299,7 kB | .jpg | 352.778 x 285.397 mm - 1000 x 809 Pixel - 72 dpi


Dimensional drawing basic component



ID: 1t2f-g02

| 44,4 kB | .cdr |
| 156,7 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 11,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi

Diagram



ID: ktf--k01

| 16,0 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 26.08.2020 12:51:45