Thermal protection

TEMPDEX 710

Temperature below 150°C | Dry environments

High dexterity and thermal protection



EN388



4111X

EN407



X1XXXX

CATEGORY 2

CE

DEXTERITY

EN ISO 21420: 5/5

SPECIFIC ADVANTAGES

Comfort

- Thin, anatomically-shaped glove ensures dexterity

Durability

- Suitable for long-term wear : excellent abrasion resistance

Skin protection

- Free of harmful substances: DMF Free

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Construction Industry (Heating engineers/Plumbers)
- Other industries
- Ceramic and plastics industry

APPLICATIONS

- Maintaining pipes, heating equipment
- Handling of composite materials after heat processing
- Handling of hot piping
- Handling of hot steel after welding
- Handling of moulds in the ceramic industry

Edit 22/12/2024

Thermal protection

TEMPDEX 710

Temperature below 150°C | Dry environments

LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	1	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Dots
Material	Nitrile sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black Yellow
European sizes	7 9 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	4.0E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.3E+12 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/3062
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 22/12/2024