STB208012

Terminal box, 200x800x120

The mild steel terminal box range, STB, with a IP 66 protection degree, is available off the shelf in many different sizes. The STB range is well suited for demanding indoor environments. Water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that, unnecessary downtime.

Feature:
IP 66 TYPE 4, 12 IK 08

CE UKCA cULus_UL Listed EAC GOST

Item no.: STB208012
EAN no.: 8713574158238

CHARACTERISTICS	
Height	200 mm
Width	800 mm
Depth	120 mm
Weight (kg)	6.30

Technical data

Material: 1.2 mm mild steel.

Body: Folded and seam welded. Four 8.5 mm diameter holes for wall fixing. Four M6 × 13 studs for bottom profiles / mounting plate fixation.

Gasket: Sealing is ensured by an injected one piece polyurethane gasket.

Earthing: M8x18 mm earthing studs in body and cover, M8 nuts, earthing washers and earthing labels.

Protection: IP 66 | TYPE 4, 12 | IK 08.

Finish: RAL 7035, structured powder coating.

Delivery: Body, cover, cover screws, fixing screws, cover plugs, and earthing facilities.

Features

Feature: Mild steel terminal box, available in a wide range of sizes, with a high IP 66 protection degree.

Advantage: Customers can choose terminal boxes that meet their size requirements, off the shelf. The installed components inside the terminal box will be safe and secure due to the high protection degree.

Benefit: Customers can receive terminal boxes with a short delivery time, that match their size requirements. This will also remove any extra costs due to oversizing. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box.

Comment: The mounting plate, BMP, and DIN profiles, BDR, mounted on profiles, BPP, have to be ordered separately, in order to complete the installation of the terminal box.