Date: 11/04/2023

A5500/1, NS100, -30...+70°C, L1=276x6mm

Bimetal thermometer, stainless steel version

Item number: 48771992

Quantity: 1 pcs.

Order code: A5500 -1-CCD-BK-B276HZZ-AHAZZZZ TB FZZZEPZSVID-AZ1ZZZZZ1ZZZZ

Overview:
A5500/1, NS100, -30...+70°C, L1=276x6mm
Process connection: plain, without thread, axial
laminated safety glass,
class 1 per EN 13190
Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
WIKA Serial number *...*

Details:
Bimetal thermometer, stainless steel version
Specifications according to data sheet: TM 55.01
Case: stainless steel
Stem material: stainless steel
Model: A 5500, nominal size 100, location of stem centre back (axial)
Connection design: 1, plain stem
Unit: °C
Scale range: -30 °C ... +70 °C
Process connection: plain, without thread
Stem diameter: 6 mm
Insertion length L1: 276 mm
Window: laminated safety glass
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Case: Stainless steel
Connector location: axial
Version: standard
Stem material: stainless steel
Permissible ambient temperature: -40 ... +70 °C
Manufacturer logo: *WIKA*
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
serial number on dial: Serial number *...*
Explosion protection: ATEX
Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.