TEGERA®





TEGERA® 12935

Learn more

SOFT PVC GLOVE, MEDIUM SLEEVE

Double-dipped PVC chemical protection glove with medium sleeve. It withstands contact heat up to 100°C/212°F, offers a good grip in oil, features a knitted lining, is phthalate-free, and has a 0.2 mm/7,8 mil chemical protection layer. Pre-curved fingers, a comfortable and soft design, lead to less hand fatigue and improved work efficiency.

CHARACTERISTICS

- Highest level of protection
- Durable
- Excellent grip
- Flexible
- Good fit
- Comfortable
- Good grip in oily environments

FUNCTIONS

- Withstands contact heat up to 100°C
- Pre-curved fingers
- Waterproof
- Protection against chemicals
- Latex-free
- Phthalate-free
- Oil and grease resistant

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Heat injuries, corrosive injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Building and construction, hvac installation, soil preparation, concrete work, wood industry work, forest work, agricultural work, gardening, marine work, fishing industry work, petro-chemical work, chemical work, chemical technology work, paper industry work, decontamination, sanitation

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, automotive, transportation

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Heat protection gloves
CATEGORY Cat. III
THICKNESS 0,2* mm (*chem-layer)
LINING MATERIAL Nylon, Seamless
LENGTH 350 mm
DEXTERITY 5
GRIP DESIGN Granulated
COLOUR Blue, Black
PAIRS PER: BUNDLE/CARTON 12/60
DIPPING MATERIAL PVC (Vinyl)
INNER MATERIAL SPECIFICATION Nylon
OUTER MATERIAL SPECIFICATION Polyvinyl chloride

COMPLIANCE

CE 0598 UKCA 0120 EAC

TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type B
KLMPT

EN ISO 374-5:2016 Virus

EN 407:2020 (No flame protection)
X1XXXX

EN 388:2016+A1:2018
4131X

EN ISO 21420:2020

FEATURES

Windproof

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	K	L	M	P	T
Permeation level	6	2	3	6	6
Degradation %	0,4	52,9	61,3	-9,6	26,8

SIZE		ARTICLE NUMBER	EAN
8	M	12935-8	7392626068520
9	L	12935-9	7392626068537
10	XL	12935-10	7392626068506
11	XXL	12935-11	7392626068513

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.