Specifications

Eaton 3-5001-007A

Catalog Number: 3-5001-007A

Eaton DM1 Variable frequency drive, 230 V AC, 3-phase, 4.8 A, 1.1 kW, IP20/NEMA0, Radio interference suppression filter, 7-digital display assembly, Setpoint potentiometer, Brake chopper, FS1



General specifications

Product Name
Eaton DM1 Variable frequency drive

Catalog Number
3-5001-007A

EAN
4015081980819

Product Length/Depth
180 mm

Product Height
152 mm

Product Width
72 mm

Product Weight
1.2 kg

Certifications
CSA-C22.2 No. 274-13
UL report applies to both US and Canada
UL
UL 508C
Certified by UL for use in Canada
IEC/EN 61800-3
CSA-C22.2 No. 274-17
IEC/EN61800-5
UL File No.: E134360
CE
RoHS, ISO 9001
IEC/EN 61800-5-1
UL Listed
CUL
IEC/EN61800-3
EAC

Powering Business Worldwide

UkrSEPRO

UL Category Control No.: NMMS,

N

C-Tick

IEC/EN 61800-2

CE marking

General

Air volume capacity

26 m³/h

Cable length

C2 ≤ 5 m, maximum motor cable length

C3 ≤ 25 m, maximum motor cable length

Communication interface

Modbus TCP, built in

CANopen®, optional

SmartWire-DT, optional

BACnet MS/TP, built in

Ethernet IP, built in

BACnet TCP

DeviceNet, optional

PROFIBUS, optional

Modbus RTU, built in

Connection to SmartWire-DT

Yes

In conjunction with DXG-NET-SWD SmartWire DT module

Degree of protection

IP20

NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Features

Parameterization: Fieldbus

Temperature-controlled fan

Parameterization: Keypad

Parameterization: Power Xpert inControl

Fitted with:

Internal DC link

IGBT inverter

Setpoint potentiometer

7-digital display assembly

Radio interference suppression filter

Brake chopper

Breaking resistance

Control unit

PC connection

Frame size

FS1

Mounting position

Vertical

Number of slots

1 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only

Safety function/level

STO (Safe Torque Off, SIL2, PLc Cat 2)

Shock resistance

0.75 mm (peak) at 10 - 57 Hz, max. 1 g at 57 - 150 Hz, according to EN 61800-5-1, EN 60068-2-6: 10 - 150 Hz

Suitable for

Branch circuits, (UL/CSA)

Climatic environmental conditions

Altitude

Max. 1000 m
Max. 3000 m
Max. 2000 m for Corner Grounded TN Systems
Above 1000 m with 1 % derating per 100 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Heat dissipation at current/speed

29 W at 25% current and 0% speed
31 W at 100% current and 50% speed
31 W at 25% current and 50% speed
38 W at 50% current and 50% speed
43 W at 50% current and 90% speed
50 W at 100% current and 0% speed
67 W at 50% current and 0% speed
84 W at 100% current and 90% speed

Input current ILN at 110% overload

9.4 A

Input current ILN at 150% overload

5.8 A

Mains current distortion

40 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

200 V

Mains voltage - max

240 V

Operating mode

PM motors

Sensorless vector control (SLV)

Speed control with slip compensation

Torque regulation

U/f control

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

240 V AC, 3-phase

230 V AC, 3-phase

Overload current IL at 110% overload

8.58 A

Overload current IL at 150% overload

7.2 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

7.8 A

Rated operational current (Ie) at 150% overload

4.8 A

Rated operational power at 220/230 V, 50 Hz, 1-phase

1.1 kW

Rated operational power at 220/230 V, 50 Hz, 3-phase, 110% overload

1.5 kW

Motor rating

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

4.2 A

Assigned motor current IM at 230 V, 50 Hz, 110% overload

6.3 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

4.6 A

Assigned motor current IM at 230 V, 60 Hz, 110% overload

6.8 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

1 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase, 110 % overload

2 HP

Braking function

Braking resistance

36 Ω

Braking torque

Adjustable to 150 %, DC - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Max. 30 % MN, Standard - Main circuit

Control circuit

Number of inputs (analog)

1

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of relay outputs

2 (parameterizable, 1 changeover contact and 1 N/O, 3 A (240 V AC) / 3 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 100 mA options incl.)

Rated operational voltage

240 V AC, 3-phase

230 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

10 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

4 kHz, 1 - 16 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

240 V

Design verification

Equipment heat dissipation, current-dependent Pvid

85 W

Rated operational current for specified heat dissipation (In)

7.8 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Dual Rating What exactly does that mean?

Electromagnetic compatibility (EMC)

Connecting drives to generator supplies

Brochures

eaton-powerxl-dm1-variable-frequency-drives-brochure-br040016en-en-us.pdf

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004864.pdf

DA-DC-00004643.pdf

Installation instructions

DM1 IL PUB 53-675 TBG Change Request 12-24-21 Final (300 DPI).pdf

Installation videos

PowerXL Variable Frequency Drive DM1

Manuals and user guides

MN040049EN

MN040060EN

mCAD model

fs1-89-1309.stp

fs1_89_1309.dwg

Multimedia

PowerXL DM1 Variable Frequency Drive - Setup via WebUI

PowerXL DM1 Variable Frequency Drive - Setup via Software

PowerXL DM1 Variable Frequency Drive - PowerXpert inControl with Bluetooth

PowerXL DM1 Variable Frequency Drive - Establishing a Modbus TCP connection with software Power Xper

PowerXL DM1 Variable Frequency Drive - Configuration with keypad

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Sales notes

eaton-powerxl-dm1-variable-frequency-drives-flyer-fl040006en-en-us.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia