Date: 12/04/2023

RLS-1000; Guide tube length: 260.0; 1 switching output

RLS-1000; Guide tube length: 260.0; 1 switching output

Item number: 48767638

Quantity: 1 pcs.

Order code: RLS-10003M301500ZZZZZZZZZZZZZZZZZZZ1DM8R026004Z2
Z1W101ARS1ZL4

Overview:
RLS-1000; Guide tube length: 260.0; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 150 mm
Electrical connection: Cable outlet PVC, IP67
Cable length: 2 m / 6.5 ft
pin assignment el. connection: see product label
Process connection: G 3/8, installation from inside
Guide tube length: 260.0 mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Ball float Ø 52 mm, 1.4571, PN40
Specifications according to data sheet: LM 50.03

Details:
RLS-1000; Guide tube length: 260.0; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 150 mm
Electrical connection: Cable outlet PVC, IP67
Cable length: 2 m / 6.5 ft
pin assignment el. connection: see product label
Process connection: G 3/8, installation from inside
Guide tube length: 260.0 mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Ball float Ø 52 mm, 1.4571, PN40
Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.