reolink	Reolink Innovation Limited		G2K4GPTSM64-UK
Picture			
Camera	**Video & Audio**	Image Sensor	1/3" CMOS Sensor
		Video Resolution	2560 x 1440 (4.0Megapixel) at 15 frames/sec
		Video Format	H.265
		Field of View	Fixed lens, Horizontal: 95°, Vertical: 57° , 115° diagonal
		Infrared Night Vision	up to 10 Meters (33ft) (LED: 6pcs/14mil/850nm)
		Digital Zoom	16x digital zoom
		Audio	Two-way audio
	PIR Detection & Alerts	Smart Alarm	PIR detection/Human Detection/Vehicle Detection
		PIR Detecting Distance	Adjustable up to 10m (33 ft)
		PIR Detecting Angle	120° horizontal
		Audio Alert	Customized verbal alerts
		Recording	Motion Triggered Recording
		Other Alerts	Instant email alerts and push notifications
	3G/4G	Frequency Bands – Europe	LTE FDD: B1/B3/B5/B7/B8/B20
			WCDMA: B1/B5/B8
		Frequency Bands – America	LTE FDD: B2/B4/B12
			WCDMA: B2/B4/B5
		Frequency Bands – Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28
			LTE TDD: B40
			WCDMA: B1/B2/B5/B8
		Transmission Data	LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)
			LTE TDD: Max 8.96Mbps(DL), Max 3. 1Mbps(UL)
			HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)
			UMTS: Max 384Kbps(DL), Max 384Kbps(UL)
	Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
		Solar	Reolink Solar Panel
		DC Power	5V/2A USB power adaptor
	Storage	Local Storage	Supports up to 128GB micro SD card(Included 64GB microSD Card)
		Cloud Storage	Supports Reolink Cloud
	Smart Home	Smart Home	Works with Google Assistant
	Working Environment	Operating Temperature	- 10 to 55° C (14° to 131° F)
		Weather Resistance	IP64 Weatherproof
	Size & Weight	Size	Φ98 x 1 12mm (Φ3.7 x 4.4 in)
		Weight (Battery included)	485 g (17. 1 oz)
	Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
Solar Panel	**Electrical Parameters**	Max Voltage	6.0V
		Max Current	530mA
		Max Power	3.2W
	Size & Weight	Dimensions	185.4x120.4x6.5(mm)
		Cable Length	4 meters (157.48in)
		Weight	280g (9.9oz)
		Interface	Micro USB Port
	Other Parameters	Working Temperature	- 10°C to 55°C (14°F to 131°F)
		Working Humidity	10%~90%
		Weather Resistance	IP65
	Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support .reolink.com/hc/en-us/