Specifications

Eaton 199398

Catalog Number: 199398

Eaton DC1 Variable frequency drive, 115 V AC, single-phase, 5.8 A, 1.1 kW, IP66/NEMA 4X, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS2



General specifications

Product Name
Eaton DC1 Variable frequency drive

Catalog Number
199398

EAN
4015081977871

Product Length/Depth
182 mm

Product Height
257 mm

Product Width
188 mm

Product Weight
3.5 kg

Certifications
UL Listed
UL File No.: E172143
Certified by UL for use in Canada
UL report applies to both US and Canada
UkrSEPRO
CSA-C22.2 No. 14
IEC/EN61800-5
UL
UL 508C
EAC
RoHS, ISO 9001
CUL
IEC/EN 61800-2
IEC/EN 61800-3
RCM
CE

Powering Business Worldwide

CE marking

UL Category Control No.: NMMS,

N

IEC/EN 61800-5-1

Features & Functions

Features

Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect mobile (App)

Fitted with:

Brake chopper

Local controls

Internal DC link

PC connection

Additional PCB protection

IGBT inverter

7-digital display assembly

Breaking resistance

UV resistance

Control unit

Functions

4-quadrant operation possible

General

Cable length

150 m, unscreened, maximum permissible cable length

100 m, screened, maximum permissible cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible cable length

Communication interface

SmartWire-DT, optional

Modbus RTU, built in

OP-Bus (RS485), built in

CANopen®, built in

Connection to SmartWire-DT

No

Degree of protection

NEMA 4X

IP66

Frame size

FS2

Climatic environmental conditions

Altitude

Above 1000 m with 1 % derating per 100 m

Max. 4000 m

Ambient operating temperature - min

-20 °C

Ambient operating temperature - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Mounting position

Vertical

Product category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

Other bus systems
MODBUS
EtherNet/IP
CAN

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments

Suitable for

Branch circuits, (UL/CSA)

Efficiency

97 % (η)

Input current ILN at 150% overload

21.9 A

Leakage current at ground IPE - max

4.8 mA

Mains switch-on frequency

Maximum of one time every 30 seconds

Mains voltage - min

110 V

Mains voltage - max

115 V

Operating mode

Sensorless vector control (SLV)
Synchronous reluctance motors
Speed control with slip compensation
PM motors
U/f control
BLDC motors

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

230 V AC, 3-phase

Overload current IL at 150% overload

8.7 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie)

5.8 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)

Rated operational voltage

115 V AC, 1-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

35 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

175 % IH

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

120 V

Motor rating

Assigned motor current IM at 230 V, 50 Hz, 150% overload

4.6 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

1.5 HP

Braking function

Braking resistance

100 Ω

Braking torque

Max. 30 % MN, Standard - Main circuit

Max. 100 % of rated operational current Ie, variable, DC - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Switch-on threshold for the braking transistor

390 VDC

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

Resources

Application notes

Starting, Stopping and Operation

Fire Mode

Connecting drives to generator supplies

Update DX-COM-STICK3

Dependency of the output current on switching frequency and ambient temperature

Conformal Coating

The OP System Bus - Parameterizing - Control

Motor data - Motor Protection - V/f curves Slip Compensation

DX-COM-STICK3_Connection

Set Point Setting

Access to Parameter Levels 2 + 3 Parameter Lock - Load Default

Electromagnetic compatibility (EMC)

How does the internal motor protection work?

I/O Configuration

PI controller

Operating Permanent Magnet and Brushless DC Motors

Operating Single Phase Motors

Low Temperature Applications

Brochures

eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004552.pdf

DA-DC-00003964.pdf

DA-DC-00004184.pdf

DA-DC-00004555.pdf

Drawings

eaton-frequency-inverter-dc1-dimensions-003.eps

Installation instructions

eaton-powerxl-dc1-ip66-instruction-leaflet-il040059zu.pdf

Installation videos

PowerXL Variable Frequency Drives DC1 and DA1 - EN

Video PowerXL DA1

Manuals and user guides

MN040059_EN

MN040003_EN

MN040022_EN

MN040018_EN

eaton-canopen-communication-manual-for-variable-frequency-drives-variable-speed-starters-da1-db1-dc1-de11-mn040019-en-us.pdf

mCAD model

e3_s2_ip66_mit_bedienelementen.stp

e3_s2_ip66_mit_bedienelementen.dwg

Multimedia

Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia