Date: 11/04/2023

S73.100/4, 0...300°C, L1=800 mmx8mm,

Gas actuated thermometer, stainless steel series

Item number:	48790028
Quantity:	1 pcs.
Order code:	S73.100-C1N-4TD-C0800-ZZZ-Z-Z-HZZ-ZZZZZZ G5 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	S73.100/4, 0...300°C, L1=800 mmx8mm, G 1/2 female axial laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °C Scale range: 0 °C ... 300 °C Connection design: 4, compression fitting, sliding on stem Process connection: G 1/2 female Stem diameter: 8 mm Insertion length L1: 800 mm Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.