Specifications

Eaton 121599

Catalog Number: 121599

Eaton Moeller® series C22 Changeover switch, With thumb-grip, maintained, 1 NC, Screw connection, 2 positions (V position), Bezel: black



General specifications

Product Name
Eaton Moeller® series C22 Changeover switch

Catalog Number
121599

EAN
4015081194179

Product Length/Depth
73 mm

Product Height
30 mm

Product Width
30 mm

Product Weight
0.023 kg

Certifications
UL File No.: E29184
UL Listed
CSA File No.: 165628
UL 508
CSA-C22.2 No. 14-05 and 94-M91
CSA certified
VDE 0660
CSA Class No.: 321103
CE marking
UL Category Control No.: NKCR
IEC/EN 60947-5-1

Catalog Notes
Contacts with safety function, by positive opening to IEC/EN 60947-5-1

Powering Business Worldwide

Product specifications

Type

Selector switch actuator

Actuator color

Black

Product Category

RMQ Compact

Features

Positive opening

Actuator function

Switching function latching

Maintained

Electric connection type

Screw connection

Fitted with:

Front ring

Operating frequency

2000 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

No

Rated impulse withstand voltage (Uimp)

4000 V AC

Actuator type

Toggle

Actuator travel and actuation force (DIN EN 60947-5-1)

4.65 mm

Force for positive opening - min

15 N

Knob travel

5.7 mm

Number of contacts (change-over contacts)

0

Resources

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004157.pdf

DA-DC-00004135.pdf

Drawings

eaton-operating-switch-changeover-switch-dimensions-002.eps

eaton-operating-switch-changeover-switch-3d-drawing.eps

eCAD model

ETN.121599.edz

Installation instructions

eaton-rmq-titan-c22-pv-compact-program-emergency-buttons-instruction-leaflet-il04716025z.pdf

Installation videos

Eaton's RMQ compact solution pilot devices

mCAD model

DA-CS-wahltaste_v

DA-CD-wahltaste_v

Sales notes

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

System overview

Pilot devices - selection aid

Wiring diagrams

eaton-operating-pushbutton-wiring-diagram-002.eps

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

0

Opening diameter

22.5 mm

Opening height

0 mm

Operating torque

0.3 Nm

Rated insulation voltage (Ui)

250 V

Bezel color

Black

Bezel material

Plastic

Design

With thumb-grip

Mounting position

As required

Rated conditional short-circuit current (Iq)

1 kA

Connection type

Screw connection

Overvoltage category

III

Degree of protection

NEMA 12

IP65

Lifespan, mechanical

1,000,000 Operations

Number of switch positions

2

Tightening torque

0.8 Nm, Screw terminals

Short-circuit protection rating

Max. 10 A gG/gL, Fuse, Contacts

Supply voltage - max

0 V

Supply voltage - min

0 V

Switching angle

60 °

Width opening

0 mm

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia