CUT PROTECTION

SKYTEC | SAPPHIRE TOTAL

OIL RESISTANT, WATER REPELLENT, CUT RESISTANT GRIP GLOVE

A great fitting, fully coated glove combining high cut and excellent grip in oily and wet conditions. Ideal for oily tasks with sharp parts that require great grip.

FEATURES

- A flexible, robust glove offering great dexterity
- Fully coated to protect the hand from oils, hydrocarbons, grease and abrasion, with optimal long lasting grip
- Extremely comfortable and great fitting
- Water repellent for working in damp or oily environments
- Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Public Works
- Transportation
- Waste Management
- Oil and Gas
- Manufacturing

Suitable Applications

- Pipe Handling
- Sharp and Oily Parts Handling
- Concreting
- Oil Submersion
- Wet Work

CERTIFICATION

EN 388:2016

4X43D

See overleaf for explanation

Globus GROUP

SKYTEC® SAPPHIRE TOTAL

SUITABLE FOR

MATERIALS	LINER:	13gg HPPE, glass, nylon, spandex
	COATING:	Double coated sandy finish nitrile over nitrile
COLOUR	Blue/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Knitted	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY00121 SKY00122 SKY00123 SKY00124 SKY00125	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- CLEANING / MAINTENANCE Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. If any damage is found on the gloves they should be disposed of. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown.
- STORAGE Ideally stored in dry conditions between 10°C and 30°C in the original packaging and sheltered from direct light. Do not exceed 40°C.
- OBSOLESCENCE When stored as recommended, the gloves will not suffer a change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and it is the responsibility of user to ascertain suitability of the glove for its intended use.
- GENERAL None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. If reaction was to occur, then obtain medical assistance.
- CAUTION! Avoid using near moving machinery due to entanglement hazard.
- PLEASE NOTE The results of the physical tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use.

CERTIFICATION LEGENDS



MECHANICAL HAZARDS
EN 388: 2016

PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

* If tests are not performed or are not applicable, 'X' will be placed instead of a number/leter

ABOUT GLOBUS

World leader in protecting hands, Globus serves organisations with bespoke hand protection solutions built from a professional range of high performance protective gloves.

Globus is proud to offer bespoke solutions that deliver robust commercial benefits not just safety improvements. We have an enviable track record in helping to reduce hand accident rates whilst delivering improved comfort and productivity as well as waste and cost reductions.

Globus applies its expertise across a spectrum of industries, meeting and exceeding a diverse range of hand protection requirements; from the rigorous demands of the petrochemical and construction industries to the complexities of clean room and aerospace manufacturing.

Find out why leading companies rely on a solution from Globus to help implement a comprehensive hand protection policy. Contact us today.

EUROPE

www.globus.co.uk

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus GROUP

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2019 Globus (Shetland) Ltd | SKY-DATA-SAPP_TOTAL-0219_1

EC compliance certificate delivered by the notified body, SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.