PRODUCT-DETAILS

OS315B22LRP

OS315B22LRP SPECIAL CONNECTED SWITCH FUSE



General Information

Extended Product Type	OS315B22LRP
Product ID	1SCA022855R0000
EAN	6417019304311
Catalog Description	OS315B22LRP SPECIAL CONNECTED SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,22 (Between the Poles),British Standard,B1-B4,Handle and shaft included,Switched - Fusible Pole

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311121D0201
Instructions and Manuals	1SCC311018M0006

Dimensions

Product Net Width	463 mm

Product Net Height	194 mm
Product Net Depth / Length	201 mm
Product Net Weight	12.58 kg 27.73 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 315 A (690 V) 315 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 100 kW (400 V) 160 kW (415 V) 180 kW (500 V) 220 kW (690 V) 315 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 315 A
Conventional Thermal Current (I_{the})	Fully Enclosed 315 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 14 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 32 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Fourth Pole Type	Switched - Fusible Pole
Switches Operating Mechanism	22 (Between the Poles)
Position of Line Terminals	Left In - Right Out
Fuse Size	B1-B4
Fuse System	British Standard
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 ... 44 N·m
Fuse Type	BS

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS315-400_LR 2016
Declaration of Conformity - CE	1SCC311121D2702
DNV GL Certificate	1SCC311132D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC311018M0006
RoHS Information	1SCC311121D2702

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	265 mm 10.43 in
Package Level 1 Depth / Length	495 mm 19.49 in
Package Level 1 Height	330 mm 12.99 in
Package Level 1 Gross Weight	12.8 kg 28.22 lb
Package Level 1 EAN	6417019304311

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnector
ETIM 5	EC001040 - Fuse switch disconnector
ETIM 6	EC001040 - Fuse switch disconnector
ETIM 7	EC001040 - Fuse switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

