www.flex-tools.com

this is proformance FLEX

# CHE 5-40 SDS-max

## Universal rotary hammer drill, 5 kg, SDS-max

## Order no. 439665

## GTIN 4030293191839




- 1150 watt hammer drill and chisel hammer in D-build with high impact energy and low vibrations
- Function switch with three functions: hammer drilling, chiselling, chisel adjustment
- Rotation stop for chiselling
- Ideal for hammer-drilling, diameter 40 mm in masonry and concrete for composite or injection anchoring systems and through-holes
- For chiselling work when removing plaster and tiles
- Variable speed, continuous adjustment from 1-6 with “Power Control LED indicator
- Safety slip clutch: offers protection if the core drill is jammed
- Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle







### Technical data

| | |
|---|---|
| Power consumption | 1150 W |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Tool holder, drill and chisel | SDS-max |
| Max. single impact energy | 10 J |
| No-load speed | 0 - 350 rpm |
| No-load blows | 1300 - 2900 1 rpm |
| Max. drilling diameter in concrete | 40 mm |
| Max. drilling diameter in masonry (drill bit) | 90 mm |
| Max. drilling diameter in wood | 32 mm |
| Max. drilling diameter in steel | 13 mm |
| Cable length | 4.0 m |
| Dimensions WxLxH | 475 x 100 x 260 mm |
| Weight | 6.4 kg |

### Standard equipment

1 Tube of grease (370894)
1 Handle
1 Carrying case