Drawer, 2 U, 3 U

for a 482.6 mm (19˝) mounting level
For front attachment to mounting angles, 482.6 mm (19˝). With cover and telescopic slides to accommodate assignment lists, operating manuals and small parts. The small version of the 2 U variant is also suitable for mounting inside a swing frame.

Material:
Sheet steel

Colour:
RAL 7035

Supply includes:
Fully assembled, including assembly parts.

Height	Clearance openings		Installation depth mm	Packs of	Model No. DK
	Width mm	Depth mm			
2 U	411	244	250	1	**7282.135**
2 U	411	419	427	1	**7282.035**
3 U	411	419	427	1	**7283.035**





Drawer for 482.6 mm (19˝)

with shelf
For keyboards, operating manuals etc. The perforated plate in the base helps air to circulate in the enclosure. Load capacity 50 kg. The 1 U drawer can be installed rotated through 180° about its longitudinal axis, allowing it to be used as a utility table.

Material:
– Drawer: Aluminium
– Telescopic slides: Sheet steel

Surface finish:
– Drawer: Anodised
– Telescopic slides: Zinc-plated

Supply includes:
Telescopic slides.

U	Packs of	Model No. PS
1	1	**4541.000**
3	1	**4542.000**

Also required:

Installation kit for enclosure system TS or installation kit, depth variable,
see page 753.



Installation kit

for component shelves and drawers, with 482.6 mm (19˝) installation in TS
For installation between the front and rear adaptor sections or adaptor pieces, 482.6 mm (19˝) in 600 mm wide enclosures.

Material:
Sheet steel

Surface finish:
Zinc-plated

Supply includes:
Assembly parts.

For enclosure system TS

For enclosure depth mm	Packs of	Model No. TS
600	1 set	**8800.560**
800	1 set	**8800.580**

Also required:

– Adaptor sections, 482.6 mm (19˝),
see page 741, or
– Adaptor pieces, 482.6 mm (19˝),
see page 742.



Installation kit, depth-variable

for 482.6 mm (19˝) component shelves and drawers
Depending on the distance between the two 482.6 mm (19˝) mounting levels, the installation kit is screw-fastened in the depth between the cranked, L-shaped mounting angles or 482.6 mm (19˝) mounting frame. Also suitable for TE.

Material:
Sheet steel

Surface finish:
Zinc-plated

Supply includes:
Assembly parts.

482.6 mm (19˝) distance between levels mm	Packs of	Model No. DK
550 – 850	2	**7063.850**

