PRODUCT-DETAILS

MLBL-05Y

MLBL-05Y LED block



General Information

Extended Product Type	MLBL-05Y
Product ID	1SFA611621R1053
EAN	7320500544785
Catalog Description	MLBL-05Y LED block
Long Description	Modular LED block - 110-130 V DC, integrated LED - Yellow - Illuminated

Ordering

E-Number (Finland)	2315767
E-Number (Norway)	4373266
E-Number (Sweden)	3705065
EAN	7320500544785
Minimum Order Quantity	10 piece
Customs Tariff Number	85369001

Dimensions

Product Net Width	0.044 m
Product Net Height	0.01 m
Product Net Depth / Length	0.035 m
Product Net Weight	0.01 kg

Container Information

Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.11 m
Package Level 1 Height	0.01 m
Package Level 1 Depth / Length	0.15 m
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	7320500373088

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Additional Information

Accessory Type	LED and lamp blocks
Color	Yellow
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm² Flexible with Ferrule 2x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm² Flexible 1x 0.75 ... 2.5 mm² Flexible 2x 0.75 ... 2.5 mm²
Connection Type	Screw Clamp
Degree of Protection	Terminals IP20
Illumination	Illuminated
Lamp Type	110-130 V DC, integrated LED
Luminance	300 millicandela
Mounting Type	Front mounting
Power Loss	Approximately 1.5 W
Product Main Type	MLBL
Product Name	LED block
Product Range	Modular range
Product Type	MLBL
Rated Current (I_n)	9.9 mA
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	110 ... 130 V DC
Recommended Screw Driver	Control Circuit Pozidriv 2
RoHS Date	0635 4
Suitable For	MP1 MP2 MP3 MP4 MPD1 MPD2 MPD3 MPD4 MPD5 MPD11 MPD12 MPD13 MPD14 MPD15 MPD16 MPM1 MPM2 KP6 MPET3 MPEP3

	MPEK3 MPET4 MPEP4 MPEK4 MPMT3 MPMT4 MPMP3 MPMP4 M2SS1 M2SS2 M2SS3 M2SS4 M2SS5 M2SS6 M3SS1 M3SS2 M3SS3 M3SS4 M3SS5 M3SS6 M3SS7 M3SS8 M3SSC1 M3SSC2 M3SSC3 M3SSC4 M3SSC5 M3SSC6 M3SSC7 M3SSC8 M2SSK1 M2SSK2 M2SSK3 M3SSK1 M3SSK2 M3SSK3 MTS1 MTS2 MTS3 MJS1 MJS2 MJS5 MJS6 MJS7 MJS8 MJS11 MJS12
Terminal Type	Screw Terminals
Tightening Torque	Control Circuit 0.9 N·m
Wave Length (λ)	588 nm
Wire Stripping Length	Control Circuit 8 mm

Certificates and Declarations (Document Number)

CQC Certificate	CQC2008010305274953
cULus Certificate	9AKK107046A9925
Data Sheet, Technical Information	1SFC151007C02__
Declaration of Conformity - CCC	2020980305001106
Declaration of Conformity - CE	2CMT2015-005452
DNV GL Certificate	E-14107
EAC Certificate	1SFC150017D1101
Environmental Information	1SFC151010D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005452

Classifications

ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC000204 - Lamp holder block for control circuit devices
ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
Object Classification Code	E
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.0 : 27371209

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Accessories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

