Specifications

# Eaton 280933

## Catalog Number: 280933

Eaton Moeller® series P5 Main switch, P5, 160 A, rear mounting, 3 pole + N, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position



## General specifications

| | |
|---|---|
| **Product Name** | **Catalog Number** |
| Eaton Moeller® series P5 Main switch | 280933 |
| **EAN** | **Product Length/Depth** |
| 4015082809331 | 150 mm |
| **Product Height** | **Product Width** |
| 150 mm | 130 mm |
| **Product Weight** | **Compliances** |
| 1.606 kg | CE Marked |

**Certifications**

UL 508
EN 60947-3
IEC 60947
CSA Std. C22.2 No. 14-05
VDE
UL Category Control No.: NLRV, NLRV7
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94
UL
VDE 0660
CSA File No.: 223805
CE
CSA
IEC/EN 60947
IEC/EN 60947-3
UL File No.: E36332
CSA Class No.: 3211-05
IEC/EN 60204

**Catalog Notes**

Rated Short-time Withstand Current (Icw) for a time of 1 second

Powering Business Worldwide

## Product specifications

### Product Category

Main switch

### Features

Version as main switch

Version as maintenance-/service switch

### Actuator color

Black

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

UV resistance only in connection with protective shield.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### Brochures

Brochure - T Rotary Cam switch and P Switch-disconnector

### Catalogs

P Switch-disconnectors and T Rotary cam switches catalogue

CA042001EN

### Declarations of conformity

DA-DC-00004899.pdf

DA-DC-00004930.pdf

### Drawings

eaton-rotary-switches-mounting-p5-main-switch-dimensions-004.eps

eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps

eaton-rotary-switches-t0-main-switch-symbol.eps

eaton-general-mounting-p1-main-switch-symbol-002.eps

eaton-rotary-switches-mounting-p1-main-switch-3d-drawing-002.eps

### eCAD model

ETN.280933.edz

### Installation instructions

IL03802011Z2021_10.pdf

### Installation videos

Eaton's P Switch-disconnectors used in a factory

### mCAD model

p5_160_v_svb_sw_n

p5_160_v_svb_sw_n.stp

### Wiring diagrams

eaton-rotary-switches-p5-main-switch-wiring-diagram-002.eps

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### Fitted with:

Black rotary handle and locking ring

### Operating frequency

50 Operations/h

### Pollution degree

3

### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

### Rated impulse withstand voltage (Uimp)

8000 V AC

### Rated permanent current at AC-21, 400 V

160 A

### Rated permanent current at AC-23, 400 V

160 A

Rated uninterrupted current (Iu)

160 A

Static heat dissipation, non-current-dependent Pvs

0 W

Switching power at 400 V

55 kW

Voltage per contact pair in series

42 V

Accessories

Auxiliary contact fitted by user.

Rated operational power at AC-3, 500 V, 50 Hz

55 kW

Device construction

Built-in device fixed built-in technique

Rated short-time withstand current (Icw)

3 kA

3 kA, Contacts, 1 second

Electrical connection type of main circuit

Frame clamp

Mounting position

As required

Actuator type

Door coupling rotary drive

Ambient operating temperature - max

50 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-25 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

10 HP

Assigned motor power at 115/120 V, 60 Hz, 3-phase

20 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

25 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

40 HP

Assigned motor power at 277 V, 60 Hz, 1-phase

25 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

60 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

60 HP

Equipment heat dissipation, current-dependent Pvid

5 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

5 W

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Rated conditional short-circuit current (Iq)

30 kA

Overvoltage category

III

Control circuit reliability

1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

Degree of protection (front side)

IP65

Number of poles

4

Mounting method

Rear mounting

Degree of protection

NEMA 12

Suitable for

Intermediate mounting

Branch circuits, suitable as motor disconnect, (UL/CSA)

Locking facility

Lockable in the 0 (Off) position

### Functions

STOP function

Interlockable

### Number of switches

1

### Safe isolation

440 V AC, Between the contacts, According to EN 61140

### Screw size

5 mm AF, Hexagon socket-head spanner, Terminal screw

### Lifespan, mechanical

100,000 Operations

### Load rating

2 x $I_e$ (with intermittent operation class 12, 25 % duty factor)

1.6 x $I_e$ (with intermittent operation class 12, 40 % duty factor)

1.3 x $I_e$ (with intermittent operation class 12, 60 % duty factor)

### Switching capacity (auxiliary contacts, general use)

10A, IU, (UL/CSA)

### Switching capacity (auxiliary contacts, pilot duty)

A600 (UL/CSA)

### Terminal capacity

2 x 25 mm², flexible with ferrules to DIN 46228

2 x 35 mm², solid or stranded

1 x 13 x 3 mm Number of segments x width x thickness, copper strip

2 x 13 x 1.5 mm Number of segments x width x thickness, copper strip

2/0 AWG, flexible

1 x 95 mm², solid or stranded

1 x 70 mm², flexible with ferrules to DIN 46228

3/0 AWG, solid or flexible conductor with ferrule

### Switching capacity (main contacts, general use)

200 A, Rated uninterrupted current max. (UL/CSA)

### Safety parameter (EN ISO 13849-1)

B10d values as per EN ISO 13849-1, table C.1

### Number of auxiliary contacts (normally open contacts)

0

### Number of contacts in series at DC-23A, 120 V

3

Number of contacts in series at DC-23A, 24 V

3

Number of contacts in series at DC-23A, 48 V

3

Number of contacts in series at DC-23A, 60 V

3

Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3)

900 A

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)

850 A

Rated breaking capacity at 500 V (cos phi to IEC 60947-3)

850 A

Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)

340 A

Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3)

1050 A

Rated operating voltage (Ue) - max

690 V

Rated operating voltage (Ue) - min

690 V

Rated operational voltage (Ue) at AC - max

690 V

Short-circuit current rating (basic rating)

10 kA, SCCR (UL/CSA)

400A Class RK1, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault)

65 kA, SCCR (UL/CSA)

300 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating

160 A gG/gL, Fuse, Contacts

Rated operational current (Ie) at AC-21, 440 V

160 A

Rated operational current (Ie) at AC-23A, 230 V

103 A

Rated operational current (Ie) at AC-23A, 400 V, 415 V

105 A

Rated operational current (Ie) at AC-23A, 500 V

106 A

Rated operational current (Ie) at AC-23A, 690 V

42 A

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

103 A

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

85 A

Rated operational current (Ie) at AC-3, 500 V

80 A

Rated operational current (Ie) at AC-3, 660 V, 690 V

42 A

Rated operational current (Ie) at DC-1, load-break switches l/r = 1 ms

160 A

Rated operational current (Ie) at DC-23A, 120 V

50 A

Rated operational current (Ie) at DC-23A, 24 V

160 A

Rated operational current (Ie) at DC-23A, 48 V

160 A

Rated operational current (Ie) at DC-23A, 60 V

160 A

Rated operational current for specified heat dissipation (In)

160 A

Rated operational power at AC-23A, 220/230 V, 50 Hz

30 kW

Rated operational power at AC-23A, 400 V, 50 Hz

55 kW

Rated operational power at AC-23A, 500 V, 50 Hz

75 kW

Rated operational power at AC-23A, 690 V, 50 Hz

37 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

45 kW

Rated operational power at AC-3, 415 V, 50 Hz

45 kW

### Rated operational power at AC-3, 690 V, 50 Hz

37 kW

### Tightening torque

125 lb-in, Screw terminals

14 Nm, Screw terminals

### Uninterrupted current

Rated uninterrupted current Iu is specified for max. cross-section.

### Rated Switching Capacity

10 HP at 120 V AC, single-phase

20 HP at 120 V AC, three-phase

25 HP at 240 V AC, single-phase

25 HP at 277 V AC, single-phase

40 HP at 240 V AC, three-phase

60 HP at 480 V AC, three-phase

60 HP at 600 V AC, three-phase

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia