


3189
OSCILLATING COMPACT ELBOW BSPP AND METRIC STUD

maximum working pressure	**bar** 20	**MPa** 2,0	**psi** 290
working temperature	**°C (Celsius)** From -20 to 80	**F (Farenheit)** From -4 to 176	**K (Kelvin)** From 253 to 353
vacuum capability	**mm Hg** vacuum level of 755,000		
body	engineering grade polymer		
sub-base	nickel-plated brass		
'O'-rings	nitrile		
gripping ring	stainless steel		



	ØD (mm)	C	E (mm)	F (mm)	ØG (mm)	H (mm)	K (mm)	L (mm)	(kg)
3189 04 10	4	G1/8	5,0	13,0	11,0	23,0	14,0	17,5	0,013
3189 04 19	4	M5x0,8	3,0	12,0	11,0	24,5	13,0	17,5	0,011
3189 06 10	6	G1/8	5,0	14,0	14,0	27,0	15,0	20,5	0,019
3189 06 13	6	G1/4	5,5	16,0	14,0	25,5	17,5	20,5	0,023
3189 06 19	6	M5x0,8	3,0	12,0	14,0	27,5	13,0	20,5	0,017
3189 08 10	8	G1/8	5,0	17,0	16,0	33,5	18,5	23,5	0,034
3189 08 13	8	G1/4	5,5	17,0	16,0	31,0	18,5	23,5	0,034
3189 08 17	8	G3/8	5,5	20,0	16,0	29,5	22,0	23,5	0,042
3189 10 13	10	G1/4	5,5	19,0	19,5	39,0	21,0	29,0	0,058
3189 10 17	10	G3/8	5,5	20,0	19,5	37,0	22,0	29,0	0,055
3189 12 13	12	G1/4	5,5	21,0	22,0	46,5	23,0	33,5	0,014
3189 12 17	12	G3/8	5,5	21,0	22,0	45,5	23,0	33,5	0,020