600-210-0AD01



Digital-Input-Modul, DC 24 V

4x

- 24 V DC input voltage
- Can accommodate 2-wire proximity sensors
- A blue LED indicates the module's operating status
- Green LEDs (one for each input) indicate the input status
- 4 inputs, electrically isolated from the backplane bus

Info

Digital input modules for the modular fieldbus IO system TB20. Note: Individual modules cannot be combined with IO systems from other manufacturers.

The scope of delivery already includes the appropriate front connector for the cabling and a base module. The module has 4 digital inputs.

Technical data

General information	
Order number	600-210-0AD01
Article name	DI 4x DC 24 V
Scope of delivery	DI 4x DC 24 V
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	4
Power dissipation	Max. 0.95 W
Input characteristic curve	Type 2, EN 61131-2
Reverse polarity protection for inputs	Yes
Hot-swap capable	Yes
Electrical isolation	
from the backplane bus	Yes
Between the channels	No
Current draw	
External	Max. 0 mA
Internal	Max. 22 mA
Input voltage	
For signal "0"	-3 V ... 9 V
For signal "1"	12 V ... 30 V
Ambient conditions	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL
UL	
Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2
CE	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration", DIN EN 60068-2-27:2010 „Shock"