Date: 06/04/2023

113.53.040 10 bar G1/8B lower mount

Pressure gauge with glycerine filling, stainless s

Item number:	12284158
Quantity:	1 pcs.
Order code:	113.53-A-BG410Z-GA-UZCZ4G-ZZZ DIAL-IAZ1ZZZZZZZZZ1Z- 1Z1ZZ9ZZZZ
Overview:	113.53.040 10 bar G1/8B lower mount class 2.5 case filling: glycerine stop-pin at zero *EN 837-1* *Cl.2.5* *WIKA*
Details:	Pressure gauge with glycerine filling, stainless s teel case, Model 113.53 Movement: copper alloy case: stainless steel ingress protection: IP 65 Bezel ring: roll formed, stainless steel Nominal size: 040 mm Unit of outer Scale: bar Measuring range: gauge pressure range Scale range: 0...10 bar Process connection: G 1/8 B Connector location: lower mount window: polycarbon Accuracy class: class 2.5 case filling: glycerine Model: 113.53 Dial description: Pressure Gauge Standard: International (standard Europe) color for 1.scale (outside): black dial background: White Manufacturer logo: *WIKA* stop pin on dial: at zero norm-mark on dial: *EN 837-1* accuracy class on dial: *Cl.2.5*

© 2023 - WIKA Instruments s.a.r.l.