REBEL™ RETRIEVAL
SELF RETRACTING LIFELINE

COMPLIANCE AND RESCUE ALL-IN-ONE





PROTECTA®

TRUSTED, QUALITY FALL PROTECTION

PRODUCT SHEET

REBEL™ RETRIEVAL SRL

COMPLIANCE AND RESCUE ALL-IN-ONE

Designed for confined space applications, the Rebel™ Retrieval SRL adds versatility and convenience to the trusted Rebel™ self-retracting lifeline range. This new model incorporates fall arrest and a built-in emergency retrieval winch for rescue, making it a versatile solution for many job sites. The Retrieval model continues the Rebel™ brand's long history of product performance and value.

Features

- 3-way emergency retrieval system
- Stowable retrieval handle
- Rugged aluminium housing
- Built-in ergonomic carrying handle
- 15m galvanised steel cable lifeline
- Swiveling self-locking snap hook with impact indicator
- Speed sensing all metal brake system
- Internal energy absorption system
- Reserve lifeline system
- Side lifeline exit with ergonomic handle
- High strength, corrosion resistant components
- Swiveling anchorage point
- Self-locking anchorage karabiner
- Optional bracket (3590498) available for easy tripod integration
- Meets or exceeds all applicable industry standards



Ready for Bracket Integration

Swivel Top (Karabiner included)

Ergonomic Carrying Handle

Stowable Retrieval Handle







Specifications:

Part Number: 3591002. ***Weight***: 11.9kg. ***Pawls***: Stainless Steel. ***Main Shaft***: Stainless Steel. ***Motor Spring***: Stainless steel. ***Fasteners***: Stainless Steel. ***Ratchet Arm***: Steel. ***Housing***: Aluminium. ***Cable:*** 5mm galvanised steel. ***Cable Bumper***: Urethane. ***Swivel Assembly***: Stainless Steel. ***Finish***: Powder Coated. ***Anchorage Karabiner***: Double action, 17.5mm gate opening, 16kN gate, 22.2kN body, steel. ***Snap Hook***: Double action with swivel & fall indicator, 19mm gate opening, 16kN gate, 23kN body, steel. ***Lifting & Lowering Ratio***: Gear Ratio 7.4:1. ***Capacity***: 140kg. ***Compatibility***: Designed for use with PROTECTA tripods, approved harnesses, components or systems, or as recommended by a competent person. ***Maximum Arresting Force***: 4kN. ***Standards***: EN 360:2002 and EN 1496:2006 class B., OSHA, ANSI Z359.14, & AS/NZS 1891.3. ***Country of Origin***: United States. ***Special Instructions/Conditions of Use***: Reading user instruction manual prior to use is essential.

PROTECTA

Capital Safety - Australia & New Zealand
Australia: 1800 245 002 I New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

Certified System — Quality ISO 9001
Certified System — Environment ISO 14001
Certified System — Health & Safety AS 4801

©2014 Capital Safety Form: 0000500AU