PSEN ml DHM down l 2.1 6O000006



Handle module for fully coded and uniquely fully coded PSENmlockswitches installed with cable outlet to the bottom, left-hand gate end stop. PU =1 door handle module with handle with yellow grip insert and handle withred grip insert (escape release handle).

Technical details

General data	
Approval:	CE, UKCA, cULus Listed, TÜV
Sensor principle:	Transponder
Coding level to ISO 14119:	hoch
Transponder coding:	fully coded
Cable exit:	nach unten
Door hinge:	links
unit type:	Betätiger
Technical data	
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
EMC to standard ...:	EN 55011: Class A, EN 60947-5-3, EN 61326-3-1
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	10g
UL enclosure type:	Type 1
Mechanical data	

Mech. service life Type 3:	6050 Zyklen
Holding force FZh slide gate:	2000 N
Holding force FZh swing gate:	3000 N
Holding force F1Max slide gate:	4000 N
Holding force F1Max swing gate:	6000 N
Max. vertical offset:	+/-2,0 mm
Max. ang. offset round X axis:	+/-2,0 deg
Max. ang. offset round Y axis:	+/-2,5 deg
Max. ang. offset round Z axis:	+/-5,0 deg
Max. offset closing direction:	+/-5,0 mm
Product material:	Zn, Kunststoff, Edelstahl
Net weight:	2050 g
Gross weight:	2450 g
Environment	
WEEE classifikation (08/2018):	0 not relevant
Commercial data	
Harmonized System Code:	85389099

Optional accessories



6O000014 PSEN ml DHM mounting flap



6O000013 PSEN ml DHM mounting plate



6O000012 PSEN ml DHM extension cover



6O000009 PSEN ml DHM extension