E1092-576 SIMULATED ROLLER ANGLE MOUNT



- All stainless steel construction
- Simulated lever actuator
- IP68 rated
- Industry standard right-angle mounting
- All brackets are fabricated form 302 or 304 stainless steel. Springs are made of 17-7ph stainless steel.

The E1092-576 is a great example of a robust limit switch with a simulated lever actuator. Completely made of high-grade stainless steel it is truly waterproof. Electromechanical endurance is customizable. CPI has achieved endurance qualifications over 5 million cycles with this basic roller limit switch design.

Typical Applications

- Cab Down Sensor
- Compartment Door Light Switch
- Dishwasher Door Closed
- Door Interlock
- Door Switch
- Dump body Detect Switch
- Hopper Down Detect
- Interlock Switches
- Interlock Switches
- Operator Presence Switch
- Outrigger Position Sensing
- Park Brake Switch
- Return to Dig Limit Switch
- Seat Position Switch
- Valve Position Sensing

Specifications	
Electrical Rating	28 VDC / 120VAC 5A resisitve, 3A inductive
Electrical Configuration	SPDT
Operating Temperature	-40 to 221°F / -40 to 105°C
Cover Material	Santoprene (thermoplastic) / bracket: 304 stainless steel
Endurance	100,000 cycles
Leads	18 AWG GXL insulated wire, 24“ / 609.6 mm length

E1092-576 SIMULATED ROLLER ANGLE MOUNT

Dimensions



