# DATASHEET - 125AMP 660V AC INDUSTRIAL FUSE



**Fuse-link, low voltage, 125 A, AC 660 V, DC 350 V, 80 kA, BS88/A4, 34 x 111 mm, gL/gG, BS**

**Part no.** 125AMP 660V AC INDUSTRIAL FUSE
**Catalog No.** TFP125

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 125 |
| Rated voltage | | | AC 660 V<br>DC 350 V |
| Construction size | | | BS88/A4 |
| Size | | | 34 x 111 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | general industrial applications |
| Standard/Approval | | | BS |
| Shape | | | offset bolted tags |
| Standards/Regulations | | | BS88-2<br>IEC 60269-2 |

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])

| | | | |
|---|---|---|---|
| Construction size | | | Other |
| Rated current | | A | 125 |
| Rated voltage | | V | 660 |
| Voltage type | | | AC/DC |
| Rated switching capacity | | kA | 80 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | None |
| Insulated metal gripping lugs (IMGL) | | | No |


© 02/2021 by Eaton Industries GmbH