URH5032

Rain hood, 500

A polyester rain hood provides shelter via a sloped roof and protects installed components from accumulated water dripping into the enclosure when the door is opened.



CHARACTERISTICS	
Width	500 mm

Item no.: URH5032
EAN no.: 8713574101548

Technical data

Description: Extra protection for outdoor use. Ventilation holes can be drilled in the top of the enclosure. When mounted, the enclosure's degree of protection is IP 44.

Material: Glass fibre reinforced polyester.

Finish: RAL 7035.

Delivery: 1 piece with mounting accessories.

Mounting requirements: Rain hoods require special wall mounting brackets UWB02. Four fixing points for securing the rain hood are marked off in the top panel. The rain hood cannot be used when the enclosures are joined, some combinations are available on request. Machining is required.

Features

Feature: Polyester rain hood for modular polyester wall mounted enclosures.

Advantage: The rain hood is mounted on top of the enclosure and provides shelter via a sloped roof both to the front and rear. The rain hood features a drip strip that protects the enclosure's door gasket from the accumulation of water.

Benefit: The rain hood protects installed components from water as it removes the risk of accumulated water on top of the gasket, dripping into the enclosure when the door is opened.

Comment: Wall mounted enclosures require machining before the rain hood can be mounted. Rain hoods are not compatible with combined enclosures. If the enclosure is to be mounted to a wall, the wall mounting brackets, UWB02, must be used. When the rain hood is mounted, the enclosure's protection degree is IP44