JEJ15
JALUNIVERS SAS ESD

S3 CI SRC
EN ISO 20345:2011
35 to 47



- **Water-repellent full grain leather**
- **Sole J&J PU / PU**
- **Safety toe cap and midsole no metallic**
- **Antistatic and dissipative**

- Low safety shoe, urban sport type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3 and EN 61340-5-1**.
- Water-repellent full grain leather upper. Reflective piping on quarters, ideal for night work. Black color.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Vamp lining in non-woven fabric, resists scuffing and acid perspiration.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Closure by 3 pairs reflective fabric loops for night visibility and one pair of lace stays. Lace-loop keeps tongue in place as you walk. Laces : 100 cm.
- **ESD** footbed single-block structure made of soft polyurethane and textile, anatomical, perforated in the font part and with heel schock absorbers.
- Ergonomic shoe with **broad synthetic polymer toe cap**, for saving on weight (50% lighter than steel). Impact resistance to **200 Joules.**
- New manufacturing **process :** antiperforation inner sole and insert in **FleXtane™ ESD By Jallatte** material, antistatic, **100% composite.** Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
  100% composite materials: lighter than steel, non-magnetic, non-conductive of heat or cold.
- Heel stiffener to reinforce the heel seat.
- Dual density **ESD** sole, the expanded molecular structure of the Softane comfort layer ensures lightweight, supple footwear for walking

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,51** (>0,32) – On the heel **0,41** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** (>0,18) – On the heel **0,28** (>0,13)

- comfort layer, density 0.45 / Outsole density = 1,10
- Heel shock absorbtion > 20 Joules.
- Highly resistant to oils and hydrocarbons.
- Abrasion resistance .
- Central stability line to maintain the foot in it's natural walking direction.
- Grip and propulsion area to respect the biomechanic of the foot and allows the movement of the walk.

Weight	Gross weight (42) : 1380 g / Net weight (42) : 1172 g		
Size	35 to 39	40 to 45	46 to 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions carton (mm)	685 x 225 x 345	685 x 440 x 345	685 x 225 x 345
Dimensions box shoe (mm)	340 x 210 x 133		



Document non contractuel
Copyright JALLATTE
Diffusion Controlée

23/11/2015

Jallatte www.jallatte.com